







RECOMMENDED HOLE LAYOUT

		1,2,17,18	NONE	45.11 [1.776]	43.18 [1.700]	17	36	5-147111-1
		1,2,17,18	NONE	45.11 [1.776]	43.18 [1.700]	17	36	147111-1
REMARKS	PLATING	ROW N	ROW M	C	B	A	NO OF POSN	PART NUMBER
		HOLD DOWN POST CONFIG LOCATION						

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. HAYMAKER 200CT98		 TE Connectivity							
		CHK J. GESFORD 200CT98									
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME ASSEMBLY, HEADER, BREAKAWAY, MOD II, DOUBLE ROW, .100 X .100 CL, RIGHT ANGLE, .025 SQUARE POSTS WITH HOLD DOWN CONFIGURATIONS							
		APVD J. GESFORD 200CT98									
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.13[.005] 4 PLC ± - ANGLES ± -		PRODUCT SPEC —									
		APPLICATION SPEC —		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO	
MATERIAL		FINISH		WEIGHT —		A2		00779		C-147111	
		SEE TABLE									
CUSTOMER DRAWING						SCALE 4:1		SHEET 1 of 1		REV D	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[147111-1](#)