

## Flange - UPCV3K-F - 1881202

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Flange, fitted on the left and right of UPCV3K 4-G-7,62, for a reliable screw connection with plugs with a screw flange

### Why buy this product

- ✔ Can be plugged into PC 4 and PC 5 plugs
- ✔ Vibration-resistant connection with flange terminal blocks that can be aligned (-F)
- ✔ For mounting on NS 35/... and NS 15... DIN rails according to EN 60715 - or for the UPCV3K 4-G-7,62 - for mounting on NS 35/... or NS 32 DIN rails
- ✔ UPCV3K provides three plug outlets per terminal point



### Key commercial data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 017918 340797
Weight per Piece (excluding packing)	12.5 g
Custom tariff number	85369010
Country of origin	Poland

### Technical data

#### General

Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0

#### Dimensions

Width	7.62 mm
Length	74.5 mm
Height NS 35/7,5	41.00 mm

#### General

# Flange - UPCV3K-F - 1881202

## Technical data

### General

Number of positions	1
---------------------	---

## Classifications

### eCl@ss

eCl@ss 4.0	27141118
eCl@ss 4.1	27141118
eCl@ss 5.0	27141118
eCl@ss 5.1	27141118
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141135

### ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897
ETIM 5.0	EC001041

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

Approval details

## Flange - UPCV3K-F - 1881202

### Approvals

EAC
-----

### Accessories

#### Accessories

#### Mounting rail

DIN rail perforated - NS 32 PERF 2000MM - 1201002



G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail, unperforated - NS 32 UNPERF 2000MM - 1201015



G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m