

Reducing adapter - REDUC-M-KV-M20/M16 - 1647611


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Step-down adapter, M20 to M16, including O-ring

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	 4 017918 941512
GTIN	4017918941512
Weight per Piece (excluding packing)	10.240 g
Custom tariff number	74153300
Country of origin	Germany

Technical data

Dimensions

Length	9 mm
Length without connecting thread	2.5 mm
Connecting thread diameter	20 mm
Hexagon angular dimension	24 mm
Length of the connecting thread	6.5 mm

Ambient conditions

Degree of protection	IP65 (Depends on the screw connection used)
Ambient temperature (operation)	-20 °C ... 80 °C

General

Reducing adapter - REDUC-M-KV-M20/M16 - 1647611

Technical data

General


Material	Nickel-plated brass
Cable gland material	Nickel-plated brass
Outer thread	M20
Internal thread	M16
Color	silver

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27439207
eCl@ss 9.0	27430314

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000938
ETIM 6.0	EC000938

Reducing adapter - REDUC-M-KV-M20/M16 - 1647611

Classifications

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408