

Left Side

Connector(s): LC-Duplex
Mode: MM
Housing Color: Beige
Geom. Spec: N/A

Fiber Path

A - ——— - B
B - ——— - A

Right Side

Connector(s): LC-Duplex
Mode: MM
Housing Color: Beige
Geom. Spec: N/A

Notes:

1. Product and Processing must meet requirements of Tyco Electronics Standard 230-702
2. Label 2 will not be present on any cable assembly less than 5 meters long.
3. Includes dust caps (not shown on print).
4. IL tested at 1300nm.

USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT. DWG NO 1906874

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

LOC: CE
DIST: 16

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A2	Rev Per EC# MINOR REVISION	6/30/2009	-	JB

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Restricted To:

DWN: Cable Assy Configurator
CHK: James Barry
APVD: James Barry
MATERIAL: -
HEAT TREAT: -

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

NAME: FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex to LC-Duplex

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 1906874	1 of 4	A2

CAC Customer Layout Rev: D

8 7 6 5 4 3 2 1

D C B A

Part #	L (meters)	L (feet)	LC-Duplex, Beige IL (dB)	LC-Duplex, Beige RL (dB)	LC-Duplex, Beige IL (dB)	LC-Duplex, Beige RL (dB)
0-1906874-1	0.950 - 1.050	3.11 - 3.44	0.5	-	0.5	-
0-1906874-2	1.950 - 2.050	6.39 - 6.72	0.5	-	0.5	-
0-1906874-3	2.950 - 3.050	9.67 - 10.00	0.5	-	0.5	-
0-1906874-4	3.920 - 4.080	12.86 - 13.38	0.51	-	0.51	-
0-1906874-5	4.920 - 5.080	16.14 - 16.66	0.51	-	0.51	-
0-1906874-6	5.920 - 6.080	19.42 - 19.94	0.51	-	0.51	-
0-1906874-7	6.920 - 7.080	22.70 - 23.22	0.51	-	0.51	-
0-1906874-8	7.920 - 8.080	25.98 - 26.50	0.51	-	0.51	-
0-1906874-9	8.850 - 9.150	29.03 - 30.01	0.51	-	0.51	-
1-1906874-0	9.850 - 10.150	32.31 - 33.30	0.52	-	0.52	-
1-1906874-1	10.850 - 11.150	35.59 - 36.58	0.52	-	0.52	-
1-1906874-2	11.850 - 12.150	38.87 - 39.86	0.52	-	0.52	-
1-1906874-3	12.850 - 13.150	42.15 - 43.14	0.52	-	0.52	-
1-1906874-4	13.850 - 14.150	45.43 - 46.42	0.52	-	0.52	-
1-1906874-5	14.850 - 15.150	48.72 - 49.70	0.52	-	0.52	-
1-1906874-6	15.840 - 16.160	51.96 - 53.01	0.52	-	0.52	-
1-1906874-7	16.830 - 17.170	55.21 - 56.33	0.53	-	0.53	-
1-1906874-8	17.820 - 18.180	58.46 - 59.64	0.53	-	0.53	-
1-1906874-9	18.810 - 19.190	61.71 - 62.95	0.53	-	0.53	-
2-1906874-0	19.800 - 20.200	64.96 - 66.27	0.53	-	0.53	-
2-1906874-1	20.790 - 21.210	68.20 - 69.58	0.53	-	0.53	-
2-1906874-2	21.780 - 22.220	71.45 - 72.90	0.53	-	0.53	-
2-1906874-3	22.770 - 23.230	74.70 - 76.21	0.53	-	0.53	-
2-1906874-4	23.760 - 24.240	77.95 - 79.52	0.54	-	0.54	-
2-1906874-5	24.750 - 25.250	81.20 - 82.84	0.54	-	0.54	-
2-1906874-6	25.740 - 26.260	84.44 - 86.15	0.54	-	0.54	-
2-1906874-7	26.730 - 27.270	87.69 - 89.46	0.54	-	0.54	-
2-1906874-8	27.720 - 28.280	90.94 - 92.78	0.54	-	0.54	-
2-1906874-9	28.710 - 29.290	94.19 - 96.09	0.54	-	0.54	-
3-1906874-0	29.700 - 30.300	97.44 - 99.40	0.55	-	0.55	-
3-1906874-1	30.690 - 31.310	100.68 - 102.72	0.55	-	0.55	-
3-1906874-2	31.680 - 32.320	103.93 - 106.03	0.55	-	0.55	-
3-1906874-3	32.670 - 33.330	107.18 - 109.35	0.55	-	0.55	-
3-1906874-4	33.660 - 34.340	110.43 - 112.66	0.55	-	0.55	-
3-1906874-5	34.650 - 35.350	113.68 - 115.97	0.55	-	0.55	-
3-1906874-6	35.640 - 36.360	116.92 - 119.29	0.55	-	0.55	-
3-1906874-7	36.630 - 37.370	120.17 - 122.60	0.56	-	0.56	-
3-1906874-8	37.620 - 38.380	123.42 - 125.91	0.56	-	0.56	-
3-1906874-9	38.610 - 39.390	126.67 - 129.23	0.56	-	0.56	-
4-1906874-0	39.600 - 40.400	129.92 - 132.54	0.56	-	0.56	-
4-1906874-1	40.590 - 41.410	133.16 - 135.85	0.56	-	0.56	-
4-1906874-2	41.580 - 42.420	136.41 - 139.17	0.56	-	0.56	-

USED ON

Qty	U of M	Description	Item No.
2	piece	Trace Label	6
4	piece	Eyelet/Shrink tube assembly - White	5
AR	meter	2 fiber, 50/125, 1.8mm, Twinzip, Violet, OFNP (Plenum)	4
4	piece	LC Connector Assy, MM	3
2	piece	LC Duplex clip, black	2
4	piece	LC, SC, FC Straight Boot, Beige	1

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A2	Rev Per EC# MINOR REVISION	6/30/2009	-	JB

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Restricted To:

DWN Cable Assy Configurator
CHK James Barry
APVD James Barry
MATERIAL -
HEAT TREAT -
AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608
NAME FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex to LC-Duplex
SCALE NTS | SIZE A2 | DRAWING NO C- 1906874 | SHEET 2 of 4 | REV A2

LOC CE
DIST 16

CAC Customer Layout Rev: D

THIS DRAWING IS A CONTROLLED DOCUMENT.
DWG NO
THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE OUTSIDE THE TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA 17105.

Part #	L (meters)	L (feet)	LC-Duplex, Beige IL (dB)	LC-Duplex, Beige RL (dB)	LC-Duplex, Beige IL (dB)	LC-Duplex, Beige RL (dB)
4-1906874-3	42.570 - 43.430	139.66 - 142.48	0.56	-	0.56	-
4-1906874-4	43.560 - 44.440	142.91 - 145.80	0.57	-	0.57	-
4-1906874-5	44.550 - 45.450	146.16 - 149.11	0.57	-	0.57	-
4-1906874-6	45.540 - 46.460	149.40 - 152.42	0.57	-	0.57	-
4-1906874-7	46.530 - 47.470	152.65 - 155.74	0.57	-	0.57	-
4-1906874-8	47.520 - 48.480	155.90 - 159.05	0.57	-	0.57	-
4-1906874-9	48.510 - 49.490	159.15 - 162.36	0.57	-	0.57	-
5-1906874-0	49.500 - 50.500	162.40 - 165.68	0.58	-	0.58	-
5-1906874-1	50.490 - 51.510	165.64 - 168.99	0.58	-	0.58	-
5-1906874-2	51.480 - 52.520	168.89 - 172.30	0.58	-	0.58	-
5-1906874-3	52.470 - 53.530	172.14 - 175.62	0.58	-	0.58	-
5-1906874-4	53.460 - 54.540	175.39 - 178.93	0.58	-	0.58	-
5-1906874-5	54.450 - 55.550	178.64 - 182.25	0.58	-	0.58	-
5-1906874-6	55.440 - 56.560	181.88 - 185.56	0.58	-	0.58	-
5-1906874-7	56.430 - 57.570	185.13 - 188.87	0.59	-	0.59	-
5-1906874-8	57.420 - 58.580	188.38 - 192.19	0.59	-	0.59	-
5-1906874-9	58.410 - 59.590	191.63 - 195.50	0.59	-	0.59	-
6-1906874-0	59.400 - 60.600	194.88 - 198.81	0.59	-	0.59	-
6-1906874-1	60.390 - 61.610	198.12 - 202.13	0.59	-	0.59	-
6-1906874-2	61.380 - 62.620	201.37 - 205.44	0.59	-	0.59	-
6-1906874-3	62.370 - 63.630	204.62 - 208.75	0.59	-	0.59	-
6-1906874-4	63.360 - 64.640	207.87 - 212.07	0.6	-	0.6	-
6-1906874-5	64.350 - 65.650	211.12 - 215.38	0.6	-	0.6	-
6-1906874-6	65.340 - 66.660	214.37 - 218.70	0.6	-	0.6	-
6-1906874-7	66.330 - 67.670	217.61 - 222.01	0.6	-	0.6	-
6-1906874-8	67.320 - 68.680	220.86 - 225.32	0.6	-	0.6	-
6-1906874-9	68.310 - 69.690	224.11 - 228.64	0.6	-	0.6	-
7-1906874-0	69.300 - 70.700	227.36 - 231.95	0.61	-	0.61	-
7-1906874-1	70.290 - 71.710	230.61 - 235.26	0.61	-	0.61	-
7-1906874-2	71.280 - 72.720	233.85 - 238.58	0.61	-	0.61	-
7-1906874-3	72.270 - 73.730	237.10 - 241.89	0.61	-	0.61	-
7-1906874-4	73.260 - 74.740	240.35 - 245.20	0.61	-	0.61	-
7-1906874-5	74.250 - 75.750	243.60 - 248.52	0.61	-	0.61	-
7-1906874-6	75.240 - 76.760	246.85 - 251.83	0.61	-	0.61	-
7-1906874-7	76.230 - 77.770	250.09 - 255.15	0.62	-	0.62	-
7-1906874-8	77.220 - 78.780	253.34 - 258.46	0.62	-	0.62	-
7-1906874-9	78.210 - 79.790	256.59 - 261.77	0.62	-	0.62	-
8-1906874-0	79.200 - 80.800	259.84 - 265.09	0.62	-	0.62	-
9-1906874-2	91.080 - 92.920	298.81 - 304.85	0.64	-	0.64	-
9-1906874-3	1.450 - 1.550	4.75 - 5.08	0.5	-	0.5	-

USED ON

DWG NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO NON-EMPLOYEES AND TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

LOC CE

DIST 16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A2	Rev Per EC# MINOR REVISION	6/30/2009	-	JB

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Restricted To:

DWN Cable Assy Configurator
CHK James Barry
APVD James Barry
MATERIAL -
HEAT TREAT -

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

NAME FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex to LC-Duplex

SCALE NTS | SIZE A2 | DRAWING NO C- 1906874 | SHEET 3 of 4 | REV A2

Label 1

Per specification 107-1645-1

XXXXXXXXXXXXXXX — Trace # - Bar Code / Trace # - Human Readable

Logo	Made in XXXX	X-XXXXXXX-X

- Trace # - Bar Code
- Trace # - Human Readable
- Part Number
- Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1

XXXXXXXXXXXXXXX — Trace # - Bar Code / Trace # - Human Readable

Logo	Made in XXXX	X-XXXXXXX-X

- Trace # - Bar Code
- Trace # - Human Readable
- Part Number
- Country of Origin

This label is used on all lengths on this drawing.

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A2	Rev Per EC# MINOR REVISION	6/30/2009	-	JB

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Restricted To:

DWN	Cable Assy Configurator
CHK	James Barry
APVD	James Barry
MATERIAL	-
HEAT TREAT	-

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

NAME: FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex to LC-Duplex

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 1906874	4 of 4	A2

LOC: CE
DIST: 16

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

CAC Customer Layout Rev: D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

1906874-2