




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) 13P AMPMODU II STIFT LEI

AMPMODU | AMPMODU Headers

1-826646-3

TE Internal Number: 1-826646-3

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **13**

Header Type **Breakaway**

Product Drawings

AMPMODU II STIFTLISTEN 90 DEG. ,EINREIHIG

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

3D PDF

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To	Printed Circuit Board
Connector Style	Plug
PCB Mounting Orientation	Vertical
Connector Type	Header
Row-to-Row Spacing	2.54 mm [.1 in]
Stabilizers	Without
Strain Relief	Without

	Board Standoff	Without
	Profile	Standard
	Product Type	Connector
	Gasket	Without
<hr/>		
Configuration Features	Number of Positions	13
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
<hr/>		
Body Features	Header Type	Breakaway
	Post Size	.63 mm [.024 in]
<hr/>		
Contact Features	Contact Protection	Without
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Thickness (µm)	.8
	Contact Mating Area Plating Material	Gold
<hr/>		
Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin Over Nickel
	Termination End Plating Thickness (µm)	3
	Termination Method to PC Board	Through Hole
<hr/>		
Mechanical Attachment	PCB Mounting Style	Straddle Mount
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Green
	Housing Material	PBT GV
<hr/>		
Dimensions	Mating Post Length	5.8 mm [.228 in]

Dimensions

Mating Post Length

5.0 mm (.220 in.)

Usage Conditions

High Temperature Housing

No

Operation/Application

High Speed Serial Data Connector

No

Industry Standards

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

500

Packaging Method

Box

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)