


FIBER COLOR	MT-RJ JACK POSITION	MT-RJ PLUG POSITION
BLUE	A	B
ORANGE OR NATURAL	B	A



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

J.W.DAVIS

27DEC07

CHK

D. FENNELL

27DEC07

APVD

D. FENNELL

27DEC07

DIMENSIONS:

METERS

TOLERANCES, UNLESS OTHERWISE SPECIFIED:

0 PLC	±	-
1 PLC	±	-
2 PLC	±	-
3 PLC	±	-
4 PLC	±	-
ANGLES	±	-
FINISH	-	-

MATERIAL

-

D. FENNELL

27DEC07

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

NAME

CABLE ASSEMBLY, 62.5/125um, OFNR, EXTENDED BANDWIDTH, MT-RJ PLUG, YELLOW SECURE TO MT-RJ JACK WITH PINS YELLOW SECURE

SIZE

A2

CAGE CODE

00779

DRAWING NO

C=1985533

RESTRICTED TO

-

SCALE

NTS

SHEET

1 of 2

REV

A

Tyco Electronics

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

BY TYCO ELECTRONICS CORPORATION.

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

CE

17

P

LTR

DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1

—

—

—

PART NUMBER

L METERS

CABLE ASSEMBLY LOSS (dB)

1985533-1

0.95-1.05

1.00

1985533-2

1.95-2.05

1.00

1985533-3

2.95-3.05

1.00

1985533-4

3.92-4.08

1.01

1985533-5

4.92-5.08

1.01

1985533-6

5.92-6.08

1.01

1985533-7

6.92-7.08

1.01

1985533-8

7.92-8.08

1.01

1985533-9

8.85-9.15

1.01

1-1985533-0

9.85-10.15

1.02

1-1985533-1

10.85-11.15

1.02

1-1985533-2

11.85-12.15

1.02

1-1985533-3

12.85-13.15

1.02

1-1985533-4

13.85-14.15

1.02

1-1985533-5

14.85-15.15

1.02

1-1985533-6

15.84-16.16

1.02

1-1985533-7

16.83-17.17

1.03

1-1985533-8

17.82-18.18

1.03

1-1985533-9

18.81-19.19

1.03

2-1985533-0

19.80-20.20

1.03

2-1985533-5

24.75-25.25

1.04

3-1985533-0

29.70-30.30

1.05

3-1985533-5

34.65-35.35

1.05

4-1985533-0

39.60-40.40

1.06

4-1985533-5

44.55-45.45

1.06

5-1985533-0

49.50-50.50

1.08

5-1985533-5

54.45-55.55

1.08

6-1985533-0

59.40-60.60

1.09

6-1985533-5

64.35-65.65

1.10

7-1985533-0

69.30-70.70

1.11

7-1985533-5

74.25-75.75

1.11

1

SEE CHART FOR APPROPRIATE CABLE ASSEMBLY LOSS AT 1300nm.

2.

MINIMUM RETURN LOSS; 20dB AT 1300nm

3.

A COPY OF TEST DATA WILL BE PLACED INSIDE OR WITH THE UNIT PACKAGE.

4.

PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TYCO ELECTRONICS STANDARD 230-702

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

J.W.DAVIS

27DEC07

CHK

D. FENNELL

27DEC07

APVD

D. FENNELL

27DEC07

DIMENSIONS:

METERS

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

MATERIAL

-

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

NAME

CABLE ASSEMBLY, 62.5/125um, OFNR, EXTENDED BANDWIDTH, MT-RJ PLUG, YELLOW SECURE TO MT-RJ JACK WITH PINS YELLOW SECURE

SIZE

A2

CAGE CODE

00779

DRAWING NO

C=1985533

RESTRICTED TO

-

SCALE

NTS

SHEET

2 OF 2

REV

A

Tyco Electronics

Tyco Electronics Corporation

Harrisburg, PA 17105-3608

1985533

AMP 3307-7 REV 31MAR2000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1985533-4](#)