




(0,50 mm) .0197"



**BSH SERIES**

# BASIC BLADE & BEAM SOCKET

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?BSH](http://www.samtec.com?BSH)

**Insulator Material:** Black LCP  
**Contact Material:** Phosphor Bronze  
**Plating:** Au or Sn over 50µ" (1,27 µm) Ni  
**Current Rating:** 2 A per pin (1 pin powered per row)  
**Flammability Rating:** UL 94 VO  
**Operating Temp Range:** -55°C to +125°C  
**Voltage Rating:** 275 VAC  
**Max Cycles:** 100  
**RoHS Compliant:** Yes

**Processing:**  
**Lead-Free Solderable:** Yes  
**SMT Lead Coplanarity:** (0,10 mm) .004" max (030-090) (0,15 mm) .006" max (120-150)  
**Board Stacking:**  
 For applications requiring more than two connectors per board or 90 positions or higher, contact [ipg@samtec.com](mailto:ipg@samtec.com)

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



## MATED HEIGHT

LEAD STYLE	MATED HEIGHT*
-01	(5,00) .197

\*Processing conditions will affect mated height.

## ALSO AVAILABLE (MOQ Required)

- 30µ" (0,76 µm) Gold
  - Edge Mount Capability
  - 8 mm, 11 mm, 16 mm, 19 mm and 22 mm Stack Height (Caution: Some automatic placement/inspection machines may have component height restrictions. Please consult machinery specifications.) (11 mm, 16 mm, 19 mm and 22 mm not available with 50 positions)
- Contact Samtec.

**Note:** Some lengths, styles and options are non-standard, non-returnable.

<b>BSH</b>	<b>NO. OF POSITIONS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>D</b>	<b>A</b>	<b>OTHER OPTION</b>
Mates with: BTH		-030, -050, -060, -090, -120, -150			-F = Gold Flash on contact, Matte Tin on tail -L = 10µ" (0,25 µm) Gold on contact, Matte Tin on tail -C* = Electro-Polished Selective 50µ" (1,27 µm) min Au over 150µ" (3,81 µm) Ni on Signal Pins in contact area, Matte Tin over 50µ" (1,27 µm) min Ni on all solder tails *Note: -C Plating passes 10 year MFG testing	
<b>AGILENT LOGIC ANALYZER TEST POINT CONNECTOR</b> Specify: ASP-65067-01						

<b>BSH</b>	<b>NO. OF POSITIONS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>D</b>	<b>RA</b>	<b>WT</b>	<b>OTHER OPTION</b>
Mates with: BTH		-030, -060, -090			-F = Gold Flash on contact, Matte Tin on tail -L = 10µ" (0,25 µm) Gold on contact, Matte Tin on tail		-GP = Guide Post