

Coupling - VS-MP-PPC/PPC-1G - 1403685

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Multi-port data coupling: for passive PROFINET cabling to robots, including mounting foot

Product description

Push/pull data coupling; version 14

Why buy this product

- Permanent mounting is also an option
- Robust design
- Including covers to protect against environmental influences



Key commercial data

Packing unit	1 pc
GTIN	 4 046356 664349
Weight per Piece (excluding packing)	247.0 g
Custom tariff number	85366990
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Mechanical characteristics

Number of positions	8
Number of slots	1
Connection profile	Data: 8-pos.
Insertion/withdrawal cycles	≥ 750 (Data)

Ambient conditions

Degree of protection	IP65
----------------------	------

Material data

Inflammability class according to UL 94	V0
---	----

Coupling - VS-MP-PPC/PPC-1G - 1403685

Technical data

Material data

Housing material	Aluminum press-drawn section / die-cast zinc
Contact material	Phosphor bronze

Electrical characteristics

Number of positions	8
Transmission characteristics (category)	CAT5

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801

ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC001134
ETIM 5.0	EC001134

UNSPSC

UNSPSC 6.01	26121616
UNSPSC 7.0901	26121616
UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121616

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Coupling - VS-MP-PPC/PPC-1G - 1403685

Approvals

Approval details

EAC

Drawings

