

Accessories
VP M20-EXE SW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



For sealing surplus threaded holes to maintain the IP class of protection

General ordering data

Type	VP M20-EXE SW
Order No.	1737080000
Version	Accessories, Blanking plug, Polyamide, RAL 9005, M 20, IP 66
GTIN (EAN)	4008190956554
Qty.	50 pc(s).

**Accessories
VP M20-EXE SW**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	19 mm	Net weight	2.9 g
--------	-------	------------	-------

Approvals

Approval for cable gland	II 2 GD, Ex d IIC, Ex e II, Ex tD
--------------------------	-----------------------------------

General information

AF size 1	23 mm	Cable gland	metric
Colour code	RAL 9005	External thread	M 20
Length of thread	15 mm	Material	Polyamide
Operating temperature range, max.	80 °C	Operating temperature range, min.	-20 °C
Pitch of thread	1.5 mm	Protection degree with GWDR	IP 68
Torque for cap nut, max.	4.6 Nm	Torque for cap nut, min.	4.6 Nm
Torque for connecting adapter, max.	4.6 Nm	Torque for connecting adapter, min.	4.6 Nm
UL 94 flammability rating	V-2		


Classifications

ETIM 3.0	EC000032	UNSPSC	30-21-18-01
eClass 5.1	27-14-91-10	eClass 6.2	27-14-91-12
eClass 7.1	27-14-91-12		

Product information

Descriptive text ordering data	Refer to the enclosed installation instructions for the tightening torque.
Descriptive text technical data	Optional sealing ring

Approvals

Approvals	
ROHS	Conform