



- | | | | | | | |
|-------------|-------------|-------------|-------------|-------------|-----|-------------|
| 59.4 [2.32] | 57.0 [2.24] | 55.6 [2.19] | 51.6 [2.03] | 46.2 [1.82] | 24 | 2-1586585-4 |
| 55.2 [2.17] | 52.0 [2.08] | 51.4 [2.02] | 47.4 [1.87] | 42.0 [1.65] | 22 | 2-1586585-2 |
| 51.0 [2.01] | 48.6 [1.91] | 47.2 [1.86] | 43.2 [1.70] | 37.8 [1.49] | 20 | 2-1586585-0 |
| 46.8 [1.84] | 44.4 [1.75] | 43.0 [1.69] | 39.0 [1.54] | 33.6 [1.32] | 18 | 1-1586585-8 |
| 42.6 [1.69] | 40.2 [1.58] | 38.8 [1.53] | 34.8 [1.37] | 29.4 [1.58] | 16 | 1-1586585-6 |
| 38.4 [1.51] | 36.0 [1.42] | 34.6 [1.36] | 30.6 [1.20] | 25.2 [0.99] | 14 | 1-1586585-4 |
| 34.2 [1.35] | 31.8 [1.25] | 30.4 [1.20] | 26.4 [1.04] | 21.0 [0.83] | 12 | 1-1586585-2 |
| 30.0 [1.18] | 27.6 [1.09] | 26.2 [1.03] | 22.2 [0.87] | 16.8 [0.66] | 10 | 1-1586585-0 |
| 25.8 [1.02] | 23.4 [0.92] | 22.0 [0.87] | 18.0 [0.71] | 12.6 [0.50] | 8 | 1586585-8 |
| 21.6 [0.85] | 19.2 [0.76] | 17.8 [0.70] | 13.8 [0.54] | 8.4 [0.33] | 6 | 1586585-6 |
| 17.4 [0.69] | 15.0 [0.59] | 13.6 [0.54] | 9.6 [0.38] | 4.2 [0.17] | 4 | 1586585-4 |
| 13.2 [0.52] | 10.8 [0.43] | 9.4 [0.37] | 5.4 [0.21] | — | 2 | 1586585-2 |
| (E) | (D) | C | B | (A) | POS | PART NUMBER |

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. HOODVER 12-NOV-2004 CHK D. COLEY 12-NOV-2004		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 P.LC ± 1 P.LC ± 2 P.LC ± 0.13 [0.005] 3 P.LC ± 4 P.LC ± ANGLES ± 0.30°		NAME APVD D. COLEY 12-NOV-2004 PRODUCT SPEC APPLICATION SPEC	
MATERIAL  FINISH		WEIGHT CUSTOMER DRAWING		SIZE A1 CAGE CODE 00779 DRAWING NO C-1586585 RESTRICTED TO	
				SCALE 5:1 SHEET 1 of 1 REV A2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1586585-4](#)