

## QUICK DISCONNECTS



## ✓ Active



## TE CONNECTIVITY (TE) FASTON 250 BENT 45DEG TAB BR LP FASTON 250

У 🖬 f v

**181948-1** TE Internal Number: 181948-1

## Always EU RoHS/ELV Compliant

Terminal Style **Tab** Mating Tab Width **6.35 mm[.25 in]** Mating Tab Thickness **.81 mm[.032 in]** Plating Material **Brass, Unplated** Mating Retention Type **Dimple** 

Product Drawings	Laston Tab PDF English
CAD Files	Customer View Model 2D_DXF.ZIP English
	Customer View Model
	3D_IGS.ZIP English
	Customer View Model
	3D_STP.ZIP <b>English</b>
	3D PDF
	PDF English
Catalog Pages/Data Sheets	1654742_HOUSEHOLD_APPLIANCES_RAST5 PDF English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Disconnect Type	Quick Disconnect
	FASTON	Yes
	Insulated Wire Support	No
	Applies To	Stud

gu.u		
	Stud Hole	Yes
	Terminal Angle	45°
	Connection Capacity	Single
Body Features	Plating Material	Brass, Unplated
Contact Features	Terminal Style	Tab
	Contact Plating Material	Unplated
Mechanical Attachment	Mating Retention Type	Dimple
Dimensions	Mating Tab Width	6.35 mm [ .25 in ]
	Mating Tab Thickness	.81 mm [ .032 in ]
	Stud Diameter	5.2 mm [ .2047 in ]
	Overall Length	16.5 mm [ .649 in ]
Operation/Application	For Housing Type	Single or Multiple
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	5000
Other	Comment	With hole for Positive Lock Receptacle
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE