




HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

06 MTE HDR SRST LATCH W/HLDWN

[AMPMODU](#) | [AMPMODU MTE](#)

103670-5

TE Internal Number: 103670-5

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Centerline **2.54 mm [.1 in]**

Number of Positions **6**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Through Hole**

Number of Rows **1**

✓ Active

↓ [PRODUCT DRAWING](#)
English

↓ [3D PDF](#)

Product Drawings

[HDR ASSY, VERT, SINGLE ROW 2.54\[.100\] CL, 0.64\[.025\] SQ POST, WITH PLZN & RETENTIVE POSTS, AMPMODU MTE](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[AMPMODU_MTE_INTERCONNECT_SYSTEM_QRG_4-1773458-0](#)

PDF
English

Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_103670-5_07082012229](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[AMPMODU MTE CONNECTORS](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Product Type	Connector
	Connector Type	Header
	Strain Relief	Without
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Plug
	PCB Orientation Feature	No
	Applies To	Printed Circuit Board

Configuration Features	Number of Positions	6
	Number of Rows	1
	Backwall/Post Interruptions	Without

Electrical Characteristics	Dielectric Withstanding Voltage	600 V
	Insulation Resistance	5000 MΩ
	Termination Resistance	15 MΩ

Body Features	Header Type	Shrouded
---------------	-------------	-----------------

Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (μ in)	15
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]
	Contact Shape	Square
	Contact Termination Area Plating Material	Tin-Lead
	Tail Plating Material	Tin-Lead
	Tail Plating Thickness	2.54 μm [100 μin]
	Contact Type	Pin
	Solder Tail Contact Plating Material	Tin-Lead
	Contact Current Rating (A)	3
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Brass

Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Alignment	Without
	Mating Retention	With
	PCB Mount Retention	With
	PCB Mount Retention Type	Hold-Down
	Contact Retention	With
	Mating Alignment Type	Latched
	Contact Retention Type	Locking Lance
	Mating Retention Type	Hold-Down
	Mating Alignment	With
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	Tail Length	3.3 mm [.13 in]
	Mating Post Length	5.84 mm [.23 in]
	PCB Thickness (Recommended)	.69 mm [.027 – .08 in]
	Height	13.59 mm [.535 in]
	Length	17.78 mm [.7 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	Receptacle Housing Assembly
	Pick and Place Cover	Without
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476
Packaging Features	Packaging Method	Tube, Tube/Box
	Packaging Quantity	30
Other	Comment	Use Keying Tool No. 91417-1 to remove post for keying.

Product Compliance

Statement of Compliance
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)