



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

250 SRS FLAG FASTON RCPT/BRASS

FASTON | FASTON Terminals and Housings

180388-2

TE Internal Number: 180388-2
 Alias ID: AMPS-0-0180388-2, C38663-000

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter **2.3 – 3.3 mm [.091 – .13 in]**

Wire Size (AWG) **20 – 15**

Wire Size (mm²) **.5 – 1.5**

Active

PRODUCT DRAWING
 English

3D PDF

Product Drawings

[.250 SERIES FLAG FASTON REC.](#)

PDF
 English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
 English

[Customer View Model](#)

3D_STP.ZIP
 English

[Customer View Model](#)

2D_DXF.ZIP
 English

[3D PDF](#)

PDF
 3D

Catalog Pages/Data Sheets

[1654742_HOUSEHOLD_APPLIANCES_RAST5](#)

PDF
 English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Wire Stop	No
Disconnect Type	Quick Disconnect
Insertion Force	Normal
FASTON	Yes
Wire/Cable Composition	Stranded
Insulated	No













	Insulated Wire Support	No
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Stud Hole	No
	Connection Capacity	Single
Body Features	Plating Material	Brass, Tin
	Fully Insulated	No
	Plating Thickness (µm)	1
Contact Features	Terminal Orientation	Flag
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Mechanical Attachment	Mating Retention Type	Dimple
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter	2.3 – 3.3 mm [.091 – .13 in]
	Wire Size (AWG)	20 – 15
	Wire Size (mm ²)	.5 – 1.5
	Overall Length	14.2 mm [.559 in]
Operation/Application	For Housing Type	Single or Multiple
Packaging Features	Packaging Method	Reel
	Packaging Quantity	4000
Other	Line	Premier
	Comment	Versions according DIN 46345

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	TOGGLE SWITCHES	THROUGH-HOLE RESISTORS	CRIMP QUICK DISCONNECTS
			
<p>.250 FLAG FAST.REC 180464-5</p>	<p>A205T1ZQ04 1-1825139-9</p>	<p>CBT 1/2 5% 22R CBT50J22R</p>	<p>110 FLAG FAST REC 22-18 PTPBR 61372-1</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>