



1-917484-3 Product Details



1-917484-3

TE Internal Number: 1-917484-3



Dynamic Series Connectors

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Dynamic Series Product Line
- D-3 Series
- Series No. = 3000
- Wire-to-Wire
- Applies To Wire/Cable

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Housings \(47\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Related Products:

- [Tooling](#)
- [Housings \(47\)](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Line = Dynamic Series
- Product Type = Contact
- [Insertion Force](#) = High
- Sealed = No
- Wire/Cable Type = Discrete Wire

Electrical Characteristics:

- Contact - Rated Current (A) = 5, 7.5
- Operating Voltage Reference = AC/DC
- Operating Voltage (VAC) = 250, 600
- Operating Voltage (VDC) = 250, 600

Termination Features:

- Wire/Cable Size (mm²) = 1.25 – 2.27
- Wire/Cable Size (AWG) = 14 – 16
- Termination Method to Wire/Cable = Crimp

Body Features:

- Wire Type = Stranded

Contact Features:

- Contact Type = Socket
- Contact Base Material = Copper Alloy
- [Contact Plating](#), [Mating Area](#), [Material](#) = Gold
- Contact Plating, Mating Area, Thickness (µm [µin]) = 0.76 [29.92]
- Multiple Contact Types = Without
- Underplate Material = Nickel
- Underplate Material Thickness (µm [µin]) = 1.30 [51.180]

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:

- Wire Range Mark = 2L

Environmental:

- Operating Temperature (°C [°F]) = -55 – +105 [-67 – +221]

Conditions for Usage:

- [Applies To](#) = Wire/Cable
- For Use With = Tab Contact
- Accepts Wire Insulation Diameter, Range (mm [in]) = 2.20 – 2.80 [0.0866 – 0.110]

Operation/Application:

- Application Use = Wire-to-Wire
- Contact Transmits (Typical Application) = Power

Packaging Features:

- Packaging Method = Reel
- Packaging Quantity = 3,000

Other:

- Series = D-3
- Series No. = 3000
- Brand = AMP

Feedback

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed



