



TERMINALS & SPLICES

## QUICK DISCONNECTS



TE CONNECTIVITY (TE)

### TAB,FASTON, .375 SERIES

FASTON | FASTON Terminals and Housings

1742375-1

TE Internal Number: 1742375-1

Always EU RoHS/ELV Compliant

Terminal Style **Tab**

Mating Tab Width **9.53 mm [ .375 in ]**

Mating Tab Thickness **1.19 mm [ .047 in ]**

Plating Material **Brass, Tin**

Underplating Material **Nickel**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**



#### Product Drawings

#### TAB, FASTON, .375 SERIES

PDF  
English

#### CAD Files

#### 3D PDF

PDF  
3D

#### Customer View Model

2D\_DXF.ZIP  
English

#### Customer View Model

3D\_IGS.ZIP  
English

#### Customer View Model

3D\_STP.ZIP  
English

Product Type Features	Wire Stop	<b>No</b>
	Disconnect Type	<b>Quick Disconnect Pin</b>
	FASTON	<b>Yes</b>
	Insulated	<b>No</b>
	Insulated Wire Support	<b>No</b>
	Applies To	<b>Stud</b>
<hr/>		
Configuration Features	Paired	<b>No</b>
	Stud Hole	<b>Yes</b>
	Terminal Angle	<b>Straight</b>
	Connection Capacity	<b>Single</b>
<hr/>		
Body Features	Plating Material	<b>Brass, Tin</b>
	Fully Insulated	<b>No</b>
	Plating Thickness (µin)	<b>150</b>
<hr/>		
Contact Features	Terminal Style	<b>Tab</b>
	Underplating Material	<b>Nickel</b>
<hr/>		
Dimensions	Mating Tab Width	<b>9.53 mm [ .375 in ]</b>
	Mating Tab Thickness	<b>1.19 mm [ .047 in ]</b>
	Material Thickness	<b>1.198 mm [ .0472 in ]</b>
	Stud Diameter	<b>4.5 mm [ .177 in ]</b>
	Overall Length	<b>25.4 mm [ 1 in ]</b>
<hr/>		
Industry Standards	UL Rating	<b>Recognized</b>
	CSA Certified	<b>Yes</b>
<hr/>		
Packaging Features	Packaging Method	<b>Bag</b>
	Packaging Quantity	<b>1000</b>
<hr/>		
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

