

Half screw connection - VC-M-KV-PG21- 1X8,5/1X12 - 1854970

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Half screw connection Pg21, made of metal, consisting of rubber seal with several holes (1 x 8.5 mm/1 x 12 mm) and one pressure screw, for type 2 - 4 housings

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	5 STK
Weight per Piece (excluding packing)	32.370 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Wrench size, union nut	30 mm
External cable diameter	8 mm ... 8.5 mm (Cable 1)
	11.5 mm ... 12 mm (Cable 2)

Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29
No. of conductors	2
Material, pressure screw	Nickel-plated brass
Seal material	TPE
Cable seal material	TPE
Shielded	No
Thread type on seal side	Pg21
Tightening torque, union nut	10.00 Nm

Half screw connection - VC-M-KV-PG21- 1X8,5/1X12 - 1854970

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC B.01742
