

## Cable gland - HC-K-KV-M40(19-28) - 1690655

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Plastic screw connection up to 5 bar, thread length: 10 mm, cable diameter: 19 - 28 mm, WAF 46, screw connection: M40

The illustration shows version HC-K-KV-M20



### Key commercial data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 017918 822699
Weight per Piece (excluding packing)	42.38 g
Custom tariff number	39269097
Country of origin	Germany

### Technical data

#### Dimensions

Wrench size, union nut	46 mm
Wrench size, support	46 mm
Length of the connecting thread	10 mm
External cable diameter	19 mm ... 28 mm

#### Ambient conditions

Degree of protection	IP68, to 5 bar
	IP68 (Up to 5 bar)
Ambient temperature (operation)	-20 °C ... 100 °C

#### General

Type of the screw connection	M40
Cable gland material	Polyamide
Seal material	Neoprene
Cable seal material	Neoprene

# Cable gland - HC-K-KV-M40(19-28) - 1690655

## Technical data

### General

Shielded	No
Thread type on connection side	M40
Tightening torque, union nut	7.50 Nm
Inflammability class according to UL 94	V2
Color	silver gray

## Classifications

### eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109

### ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Approvals

### Approvals

---

#### Approvals

EAC

---

#### Ex Approvals

---

# Cable gland - HC-K-KV-M40(19-28) - 1690655

## Approvals

Approvals submitted

## Approval details

EAC

## Drawings

Dimensioned drawing

