


## 1-1634629-0 Product Details

**Have a Question?**  
 Chat with a Product Information Specialist



1-1634629-0

TE Internal Number: 1-1634629-0

Active

### BNC RF Connectors

Always EU RoHS/ELV Compliant ([Statement of Compliance](#))

#### Product Highlights:

- Connector - RF
- Jack
- Connector Style = Jack
- Applies To Printed Circuit Board
- Body Style = Straight

[View all Features](#)

#### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Add to My Part List Request Sample Find Similar Products Buy Product

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">BNC STRAIGHT INSULATED PCB SOCKET 75 OHM WHITE</a> (PDF, English)</li> <li>• <a href="#">BNC STRAIGHT INSULATED PCB SOCKET 75 OHM BLACK</a> (PDF, English)</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Type</a> = Connector - RF</li> <li>• Gender = Jack</li> <li>• <a href="#">Body Style</a> = Straight</li> <li>• <a href="#">PCB Mount Angle</a> = Vertical</li> <li>• <a href="#">Grade</a> = Commercial</li> <li>• <a href="#">PCB Height (mm [in])</a> = 34.90 [1.374]</li> <li>• <a href="#">PCB Mount Retention</a> = With</li> <li>• Mounting Post Style = Round</li> <li>• Mounting Post Length (mm [in]) = 4.30 [0.169]</li> <li>• <a href="#">Body Material</a> = Zinc</li> <li>• <a href="#">Body Insulation</a> = With</li> <li>• <a href="#">Sealed</a> = No</li> <li>• <a href="#">Isolated</a> = No</li> <li>• <a href="#">Dielectric Material</a> = Polyethylene</li> <li>• For Use With = ZDC/BNC Connector</li> <li>• <a href="#">Color</a> = Black</li> <li>• Number of Ports = 1</li> <li>• Panel Thickness (mm [in]) = 1.50 - 5.50 [0.059 - 0.217]</li> <li>• Solder Terminal = With</li> </ul> <p><b>Mechanical Attachment:</b></p> <ul style="list-style-type: none"> <li>• Surface Mountable = No</li> <li>• <a href="#">Panel Attachment</a> = With</li> <li>• <a href="#">Panel Attachment Method</a> = Bulkhead, Hex Nut</li> <li>• Panel Attachment Style = Rear Mount</li> <li>• Panel Cutout = 12.0mm x 12.9mm D-Shape</li> <li>• Flange and Thread Material = PBT Polyester</li> <li>• Flange and Thread Material Color = Black</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Connector Impedance (Ω)</a> = 75</li> </ul>	<p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Hardware Included</a> = No</li> <li>• PCB Mount Retention Type = Solder Tail (Pin)</li> <li>• <a href="#">Body Plating</a> = Nickel</li> <li>• <a href="#">Polarized</a> = No</li> <li>• PCB Tail Length (mm [in]) = 4.30 [0.169]</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Center Contact Material</a> = Brass</li> <li>• <a href="#">Center Contact Plating</a> = Gold</li> </ul> <p><b>Housing Related Features:</b></p> <ul style="list-style-type: none"> <li>• Connector Style = Jack</li> <li>• Housing Material = PBT - GF</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• Government/Industry Qualification = No</li> <li>• <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>• RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Applies To</a> = Printed Circuit Board</li> <li>• PCB Thickness, Recommended (mm [in]) = 3.20 [0.126]</li> <li>• Operating Temperature (Max.) (°C) = 85</li> </ul> <p><b>Packaging Related Features:</b></p> <ul style="list-style-type: none"> <li>• Packaging Method = Individual</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Greenpar</li> </ul>

BOOKMARK

<p><b>Corporate Information</b></p> <ul style="list-style-type: none"> <li>Who We Are</li> <li>Investors</li> <li>News Room</li> <li>Supplier Portal</li> <li>Careers</li> </ul>	<p><b>Quick Links</b></p> <ul style="list-style-type: none"> <li>Check Distributor Inventory</li> <li>Cross Reference</li> <li>Find Documents &amp; Drawings</li> <li>Product Compliance Support Center</li> <li>Site Map</li> </ul>	<p><b>Customer Support</b></p> <ul style="list-style-type: none"> <li>Email or Chat with Us</li> <li>Find a Phone Number</li> <li>Search Knowledge Base</li> <li>Manage Your Account</li> </ul>	<p><b>Sign up for our eNewsletter</b></p> <p>Enter your email address <input type="text"/> </p> <p><b>Follow Us On:</b></p> <p> </p> <p><b>Visit Us On:</b></p> <p></p>
--	--	---	---