

Protective covers - HC-B 24-TMS-SD-IP66 - 1411520


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON ADVANCE, IP66, B24 protective cover for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet: 3 mm



Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 918732
Weight per Piece (excluding packing)	63.16 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Ambient conditions

Degree of protection of housing (IP)	IP66
Ambient temperature (operation)	-20 °C ... 100 °C

General

Type	B24 HC-ADVANCE protective cover
Housing type	Protective cover
Color	gray
Locking type	Screw locking
Torque	2 Nm (Locking screw)
Seal material	NBR
Material lock	High-grade steel
Material of locking screw	High-grade steel
Material, protective cover	PA
Flammability rating according to UL 94	V0
Assembly instructions	Tightening torque of locking screw: 3 Nm

Protective covers - HC-B 24-TMS-SD-IP66 - 1411520

Classifications

eCl@ss

eCl@ss 4.0	27141210
eCl@ss 4.1	27141210
eCl@ss 5.0	27149110
eCl@ss 5.1	27149110
eCl@ss 6.0	27261210
eCl@ss 7.0	27440208
eCl@ss 8.0	27440208

ETIM

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002314
ETIM 5.0	EC002314

UNSPSC

UNSPSC 6.01	30212113
UNSPSC 7.0901	39121712
UNSPSC 11	39121712
UNSPSC 12.01	39121712
UNSPSC 13.2	39121712

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Protective covers - HC-B 24-TMS-SD-IP66 - 1411520

Dimensional drawing

