

Sleeve housing - VC-K-T2-R-M25 - 1855107

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing, plastic, with metric cable outlet, locking screws with knurled head, type: VC2, cable screw connection: M25

Why buy this product

- Seals with two cable entries are available
- Angled cable outlet so the cable can be routed as desired, from the side and straight



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| GTIN |  4 017918 970864 |
| Weight per Piece (excluding packing) | 54.22 g |
| Custom tariff number | 85472000 |
| Country of origin | Poland |

Technical data

Dimensions

| | |
|--------|-------|
| Height | 65 mm |
|--------|-------|

Ambient conditions

| | |
|---------------------------------|------------------|
| Degree of protection | IP65 |
| Ambient temperature (operation) | -40 °C ... 80 °C |

General

| | |
|---|---|
| Note | When using fiber optics, the bending radii of the cable manufacturers must be observed. |
| Type | VC2 |
| Degree of protection | IP65 |
| Inflammability class according to UL 94 | V0 |
| Locking type | Screw locking, knurled head |
| Fixing screws | M4 |

Sleeve housing - VC-K-T2-R-M25 - 1855107

Technical data

General

| | |
|-----------------------------------|---------------------|
| Tightening torque, mounting screw | 1.5 Nm \pm 0.3 Nm |
| Type of the screw connection | M25 |
| Pg screw connection | none |
| Cable exit | Angled |
| Housing material | Polyamide |
| Seal material | EPDM |
| Ambient temperature (operation) | -40 °C ... 80 °C |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27371205 |
| eCl@ss 5.1 | 27371205 |
| eCl@ss 6.0 | 27371205 |
| eCl@ss 7.0 | 27371205 |
| eCl@ss 8.0 | 27440202 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 31261501 |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Sleeve housing - VC-K-T2-R-M25 - 1855107

Approvals

Approvals submitted

Approval details

| |
|-----|
| EAC |
|-----|

Accessories

Accessories

Full screw connection

Cable gland - HC-K-KV-M25(11-17) - 1690639



Plastic screw connection up to 5 bar, thread length: 8 mm, cable diameter: 11 - 17 mm, WAF 29, screw connection: M25

Marking label - VC-BZS WH - 1852875



Marker labels, unprinted, 5-section, for individual labeling with M-PEN or CMS system, white

Drawings

Dimensioned drawing

