


HC-B 24-KML-80/M1M40

Order No.: 1586701



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1586701>

Coupling housing, with single locking latch, height 79 mm, without screw connection, 1x M40

Commercial data	
GTIN (EAN)	 4 046356 426794
Note	Made-to-order
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 497 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
06/18/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.


Technical data

General data	
Note	For contact inserts HC-B24, BB46, D64, DD108, M
Design	B24
Height	79 mm
Width	43 mm
Length	120 mm

Locking type	With single locking latch
Type of the screw connection	1x M40
Wrench size, union nut	40 mm
External cable diameter	18 mm ... 32 mm
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Cable gland material	Nickel-plated brass
Cable seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;