


General ordering data

Order No.	1896800000
Part designation	HDC HA 16 FT
Version	HDC insert, Socket, 250 V, 22 A, Poles: 16 + PE, Tension clamp connection, BG: 5
EAN	4032248592401
Qty.	1 pc(s).

Product notes

Function	Assignment 1-16
Note, accessories	SD 0.6 x 3.5

General data

Colour	beige
Insulating material group	IIIa
Insulation material	PC glass-fibre reinforced (UL-listed and railway-certified)
Insulation resistance	$10^{10} \Omega$
No. of poles, total	16 + PE
Plugging cycles, silver	≥ 500
Pollution severity	3
Temperature, max.	125 °C
Temperature, min.	-40 °C
UL 94 flammability class	V-0
Size	5
Series	HA
Type	Socket
Type designation	HA 16

Connection data PE

Rated cross-section	2.5 mm ²
Fixing screw	M 4
Min. tightening torque	1.2 Nm
Blade size, crosshead	size PH1
Max. tightening torque	1.5 Nm

Connection data PE

Blade size, slotted	SD 0.8 x 4.0
Stripping length	10 mm
Max. connection cross-section, solid	0.5 mm ²
Min. connection cross-section, solid	2.5 mm ²
Min. connection cross-section, stranded	0.5 mm ²
Connection type PE	Screw connection
Max. connection cross-section, stranded	2.5 mm ²
Min. connection cross-section "f" with wire end ferrule	0.5 mm ²
Max. connection cross-section "f" with wire end ferrule	2.5 mm ²
AWG, min.	AWG 20
AWG, max.	AWG 14

Rating data

Rated voltage (DIN EN 61984)	250 V
Rated current (DIN EN 61984)	22 A
Rated voltage according to UL/CSA	600 V AC/DC
Rated impulse voltage (DIN EN 61984)	4 kV

Version

Type of connection	Tension clamp connection
Blade size, slotted	SD 0.6 x 3.5
Stripping length	8 mm
Material	copper alloy
Connection cross-section, min.	0.5 mm ²
Connection cross-section, max.	2.5 mm ²
AWG, min.	AWG 20
AWG, max.	AWG 14
Size	5
Surface finish	Silver passivated
Volume resistance	≤ 2mΩ

Approvals

Approvals institutes

**Downloads**

PDF 1896800000_HDC_HA_16_FT_STP_Blatt__1.pdf

Downloads

DXF	1896800000_HDC_HA_16_FT_STP_Blatt__1.dxf
IGES	1896800000_HDC_HA_16_FT_STP.igs
STEP	1896800000_HDC_HA_16_FT_STP.stp
VRML	1896800000_HDC_HA_16_FT_STP.wrl

Classifications

ETIM 2.0	EC001121
ETIM 3.0	EC001121
eClass 4.1	27-14-08-05
eClass 5.0	27-14-34-19
eClass 5.1	27-14-34-19

Similar products

Order No.	Part designation	Version
1896780000	HDC HA 10 FT	HDC insert, Socket, 250 V, 22 A, Poles: 10 + PE, Tension clamp connection, BG: 2
1896790000	HDC HA 10 MT	HDC insert, Pin, 250 V, 22 A, Poles: 10 + PE, Tension clamp connection, BG: 2
1896830000	HDC HA 16 MT	HDC insert, Pin, 250 V, 22 A, Poles: 16 + PE, Tension clamp connection, BG: 5
1896810000	HDC HA 16 FT 17-32	HDC insert, Socket, 250 V, 16 A, Poles: 16 + PE, Tension clamp connection, BG: 5
1896840000	HDC HA 16 MT 17-32	HDC insert, Pin, 250 V, 16 A, Poles: 16 + PE, Tension clamp connection, BG: 5
1896820000	HDC HA 16 FT 33-48	HDC insert, Socket, 250 V, 16 A, Poles: 16 + PE, Tension clamp connection, BG: 5
1896850000	HDC HA 16 MT 33-48	HDC insert, Pin, 250 V, 16 A, Poles: 16 + PE, Tension clamp connection, BG: 5