

## HC-HV 3-KMQ-73/M1PG16

Order No.: 1773682

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1773682>

Coupling housing, with double locking latch, height 52 mm, with screw connection, 1x Pg16

Commercial data	
GTIN (EAN)	4017918115746
Note	Made-to-order
sales group	D003
Pack	10 pcs.
Customs tariff	85389099
Weight/Piece	0.2478 KG
Catalog page information	Page 245 (PC-2005)

**Product notes**

WEEE/RoHS-compliant since:  
03/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data**

General data	
Note	For contact inserts HV-HV3
Design	HV3
Height	73 mm
Width	43 mm
Length	73 mm

Housing type	Coupling housings
Locking type	With double locking latch
Type of the screw connection	1x Pg16
Pg screw connection	With
Wrench size, union nut	22 mm
External cable diameter	7.5 mm ... 15 mm
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Cable gland material	Nickel-plated brass
Cable seal material	NBR
Material lock	High-grade steel
Material grip body interlock	PA-GF

#### Certificates / Approvals



Certification

GOST

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;