


HC-B 32-TFQ-80/O1PG21G

Order No.: 1675065

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1675065>

Sleeve housing, for double locking latch, height 80 mm, without screw connection, 1x Pg21, straight cable entry

Commercial data

GTIN (EAN)	 4 017918 149826
Note	Made-to-order
sales group	D002
Pack	10 pcs.
Customs tariff	85389099

Product notesWEEE/RoHS-compliant since:
01/31/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General data**

Note	For contact inserts HC-B32, DD144, M
Design	B32
Height	80 mm
Width	79 mm

Length	94 mm
Housing type	Sleeve housings
Locking type	For double locking latch
Cable exit	Straight
Pg screw connection	None
Type of the screw connection	1x Pg21
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray

Certificates / Approvals




Certification

GOST

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;