


Male Style F


Series 8487 – 3 rows (3 x 16)



| Contact Design and Termination Length | Number of Contacts | Loading Description | Part Number Performance classes according to DIN 41612 | |
|-------------------------------------------|--------------------|-----------------------------------|--------------------------------------------------------|---------------------|
| | | | II | I |
| 3.0 mm (Y) Right Angled Pitch 5.08 | 32 | d + z fully loaded | 10 8487 048 001 026 | 10 8487 048 001 050 |
| | 32 | b + z fully loaded | 10 8487 048 001 029 | 10 8487 048 001 053 |
| | 32 | d + z fully, Ground in z2 | 59 8487 048 000 055 | 59 8487 048 000 061 |
| | 32 | d + z fully, Ground in z2 + z32 | 59 8487 048 000 056 | 59 8487 048 000 062 |
| | 32 | b + z fully, Ground in z2 | 59 8487 048 000 057 | 59 8487 048 000 063 |
| | 32 | b + z fully, Ground in z2 + z32 | 59 8487 048 000 058 | 59 8487 048 000 063 |
| | 48 | d + b + z fully loaded | 10 8487 048 001 025 | 10 8487 048 001 049 |
| | 48 | fully loaded + Ground in z2 | 59 8487 048 000 053 | 59 8487 048 000 059 |
| | 48 | fully, Ground in z2 + z32 | 59 8487 048 000 054 | 59 8487 048 000 060 |
| | 48 | fully loaded + Ground in b2 + b32 | 59 8487 048 000 066 | 59 8487 048 000 065 |
| | 48 | fully loaded + Ground in d2 + d32 | 59 8487 048 000 069 | 59 8487 048 000 068 |

NB: Alternative Prefix Variations Available: 16, please refer to Page 10.
 Additional Plating & Loading Variations: Please contact your local AVX sales office or distributor.

LOADING DESCRIPTION



△ denotes ground pin

DIMENSIONS

