

## Docking frames - HC-B 16-ANDOCK-MOD-A - 1587467

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Docking frame for four module slots, fixed assembly, plastic without PE, rack compensation of +/-2.0 mm in the x/y-axis, for M4 cylinder head screws

### Product Description

Docking frame, permanently fitted, made from plastic without PE. Slide-in offset x/y axis  $\pm 2.0$  mm.

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	2 STK
GTIN	 4 046356 526425
GTIN	4046356526425
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### General

Material	PC
Flammability rating according to UL 94	V0
Design	B16
Assembly instructions	Due to the plastic frame without PE, a metal attachment panel must be grounded separately.
Connection	Floating fixing with special washer (Order No. 1587496) and standard M4 screws/nuts, screw length: 6 mm + panel thickness + (locking nut in the case of panel without thread). 2 mm play.

### Standards and Regulations

# Docking frames - HC-B 16-ANDOCK-MOD-A - 1587467

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Approvals

### Approvals

---

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		7500651.22.01.00246
-----	---	---------------------

---