

All categories

Search term



Your shopping cart

Products

MyHARTING

Downloads / Catalogue order

Reparservice

Han-Eco 16B-C-DL

[Spotted an error?](#) | [Print page](#) | [Back](#)

Image is for illustration purposes only.
Please refer to product description.

[Features](#)[Material properties](#)[Dimensions and weight](#)[Version](#)[Norms and specifications](#)

| | |
|---------------------|---------------------|
| Part number: | 19 41 016 5406 |
| Description: | Han-Eco 16B-C-DL |
| Type sheet: | PDF |

[Login to MyHARTING](#)
for pricing and stock checkQuantity: [Shopping cart](#)[Email inquiry](#)

Need assistance?

**Customer service****Your HARTING customer
service representative:****866-278-0306**[CustomerService-USA@HA ...](mailto:CustomerService-USA@HA...)

Catalogue

Industrial Connectors Han® -
Page 702[Browse](#)[Download](#)

Catalogue

Chapter Han-Eco® - Page 18

[Browse](#)[Download](#)

Features

| | |
|------------------------------------|-------------------------------------|
| RoHS conformity: | Please contact our customer service |
| Size: | 16 B |
| Material, locking lever: | polyamide, fibre-glass reinforced |
| Lever type: | double locking lever |
| Type of hood/housing: | Protection cover for hoods |
| Series: | Han-Eco® |
| Limiting temperature, min.: | -40 °C |
| Limiting temperature, max.: | 125 °C |

[Top](#)

Material properties

| | |
|---------------------------------|-----------------------------------|
| Colour, locking element: | RAL 9005 (black) |
| Material, seal: | NBR |
| Colour, hood/housing: | RAL 9005 (black) |
| Material, hood/housing: | polyamide, fibre-glass reinforced |

[Top](#)

Dimensions and weight

| | |
|--------------------|--------|
| Net Weight: | 85.6 g |
|--------------------|--------|

[Top](#)

Version

| | |
|---|--|
| Hoods and Housings: Case of operation: | Plastic hoods/housings for industrial applications |
|---|--|









[Top](#)

Norms and specifications











| | |
|--|-----------|
| Flammability acc. to NFF 16 101 / 16 102: | F2 / I3 |
| Flammability locking lever acc. to UL 94: | V 0 |
| Flammability hoods/housings acc. to UL 94: | V 0 |
| Approval GL: | Yes |
| Degree of protection acc. to DIN EN 60 529: | IP65 |
| Specification: | IEC 61984 |

[Top](#)

Downloads

| Title | Download |
|---------------------------------------|--|
| Type sheet |  PDF |
| Type sheet |  DXF |
| CAD data 3D |  IGES |
| CAD data 3D |  STEP |
| CAD data 3D |  VRML |
| CAD data 3D |  JT |
| Industrial Connectors Han® - Page 702 |  PDF |
| Chapter Han-Eco® - Page 18 |  PDF |

Recently viewed - [Delete](#)

| | |
|---|--|
|  <p>Han-Eco 16B-C-DL</p> <p>Show product details</p> |  <p>Han-Eco 16B asg1 M40 with cable gland</p> <p>Show product details</p> |
|  <p>Han-Modular ECO hood IP65 (without PE)</p> <p>Show product details</p> |  <p>Han-Eco 10B coupler with M32 cable gland</p> <p>Show product details</p> |
|  <p>Han-Modular ECO base panel (with PE mark)</p> <p>Show product details</p> |  <p>Han-Eco 10B SM Hsg 1x M32 w/cable gland</p> <p>Show product details</p> |
|  <p>Han-Eco 6B SM Hsg 1x M32 w/cable gland</p> <p>Show product details</p> |  <p>Han-Modular ECO hood IP20 (with PE mark)</p> <p>Show product details</p> |
|  <p>Han-Eco 16B SE M40 with cable gland</p> <p>Show product details</p> |  <p>Han-Eco 16B-HBM</p> <p>Show product details</p> |

Recently searched - [Delete](#)

- All categories: [09140010423](#) (1)
- All categories: [09302100803](#) (1)
- All categories: [19302160252](#) (1)
- All categories: [19302240292](#) (1)
- All categories: [11000009601](#) (1)
- All categories: [19410060301](#) (1)
- All categories: [han_eco](#) (188)
- All categories: [19410012700](#) (1)
- All categories: [yellock](#) (164)

Website support: | **E-mail address** (For technical problems regarding the website)

