

All categories

Search term



Your shopping cart

Products

MyHARTING

Downloads / Catalogue order

Repairstervice

Han 24B-HMC-asg1-LB-M25

[Spotted an error?](#) | [Print page](#) | [Back](#)

Image is for illustration purposes only.
Please refer to product description.

Combinables

[Features](#)[Dimensions and weight](#)[Norms and specifications](#)[Material properties](#)[Version](#)

Part number: 19 30 224 1251
Description: Han 24B-HMC-asg1-LB-M25
Type sheet: [PDF](#)

[Login to MyHARTING](#)
for pricing and stock check

Quantity: [Shopping cart](#)[Email inquiry](#)

Need assistance?



Customer service

Your HARTING customer
service representative:

866-278-0306

[CustomerService-USA@HA ...](mailto:CustomerService-USA@HA...)

Catalogue

Industrial Connectors Han® -
Page 535

[Browse](#)[Download](#)

Features

Mating cycles: >= 10,000
Han-Easy Lock®: Yes
RoHS conformity: Yes
Size: 24 B
Material, locking lever: polycarbonate + stainless steel
Lever type: single locking lever
Type of hood/housing: Surface mounted housings
Series: Han® B HMC
Limiting temperature, min.: -40 °C
Limiting temperature, max.: 125 °C

[Top](#)

Material properties

Colour, locking element: RAL 7037 (grey)
Surface, hood/housing: powder-coated
Material, seal: NBR
Colour, hood/housing: RAL 7037 (grey)
Material, hood/housing: aluminium die-cast

[Top](#)

Dimensions and weight

Net Weight: 319.9 g

[Top](#)

Version

Hoods and Housings: Case of operation: Metal hoods/housings for industrial applications
No. of cable entries: 1
Size: M25
Cable entry: side entry
Style: Low construction

[Top](#)

Norms and specifications

Flammability locking lever acc. to UL 94: V 0
Protection class acc. to UL 50: NEMA type 4/4X/12
Approval GL: Yes

Downloads

Title	Download
Type sheet	PDF
Type sheet	DXF
Type sheet	CGM
CAD data 3D	STEP
CAD data 3D	JT
Industrial Connectors Han® - Page 535	PDF

Combinables

Image	Part number	Description	Tech. info	Quantity
	09 30 224 0803	Han B Hood HC 2 Reels without PG		1 Shopping cart
	19 30 224 0447	Han 24B-HMC-gg-R-M32		1 Shopping cart
	19 30 224 0448	Han 24B-HMC-gg-R-M40		1 Shopping cart
	19 30 224 0547	Han B Hood Side Entry HC 2 Reels M32		1 Shopping cart
	19 30 224 0548	Han 24B HMC-gs-R-M40		1 Shopping cart
	19 30 224 1541	Han 24B-HMC-gs-R-M25		1 Shopping cart
	19 30 224 1542	Han 24B-HMC-gs-R-M32		1 Shopping cart

Recently viewed - [Delete](#)

 Han 24B-HMC-asg1-LB-M25 Show product details	 Han E HMC female contact Au AWG 19 Show product details
 Han 10B-HMC-asg1-LB-M20 Show product details	 Han D F crimp contact 2,5 mm² Au/HMC Show product details

Recently searched - [Delete](#)

All categories: [09302100803](#) (1)
All categories: [19302160252](#) (1)
All categories: [19302240292](#) (1)
All categories: [11000009601](#) (1)
All categories: [19410060301](#) (1)
All categories: [han eco](#) (188)
All categories: [19410012700](#) (1)
All categories: [yellock](#) (164)

**Han E HMC female
contact Au AWG 18**

[Show product details](#)

**Han 16B-HMC-kg-LB-
M32**

[Show product details](#)



**Han 10B-HMC-asg2-LB-
M20**

[Show product details](#)



**Han 24B-HMC-kg-LB-
M32**

[Show product details](#)



**Han E HMC male contact
Au AWG 12**

[Show product details](#)



**Han D F crimp contact
0,75 mm² Au/HMC**

[Show product details](#)



ABOUT SSL CERTIFICATES

[Home](#) | [Contact](#) | [Privacy Policy](#) | [Terms of Use](#) | [Sales and delivery conditions](#) | [Imprint](#)

HARTING contact: HARTING Inc. of N.America | Bowes Road1370 | 60123-5538 Elgin | USA
HARTING support: 866-278-0306 | **E-mail address** (For questions regarding products, orders and user accounts)
Website support: | **E-mail address** (For technical problems regarding the website)

Follow us on

