

HC-B 6-TMS-100/O1STM20G-STAIM


Order No.: 1637032

The figure shows the version with standard screw locking



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1637032>

HEAVYCON ADVANCE STA sleeve housing B6, with screw locking, height 100 mm, with 1x M20 thread, straight cable outlet, with M6 x 18 hexagonal socket-head screws made of high-grade steel in acc. with DIN EN ISO 4762

Commercial data	
GTIN (EAN)	 4 046356 092005
Note	Made-to-order
sales group	D201
Pack	10 pcs.
Customs tariff	85369010

Product notes

WEEE/RoHS-compliant since:
01/31/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Accessories

Item	Designation	Description
Assembly		
1686533	HC-B-AF	Panel mounting flange for HEAVYCON-ADVANCE TMS housing with screw locking


1604638	HC-B-AF-SET	Panel mounting flange for screw locking, set comprising 2 panel mounting flanges with 4 self-tapping Torx head screws and 4 fan-type washers
---------	-------------	--

General

1690736	HC-B 6-TMS-SD-IP50	HEAVYCON ADVANCE IP50 protective cover B6, for panel mounting side, with clip locking, with retaining cord, diameter of retaining cord eyelet 3 mm
1690778	HC-B 6-TMS-SD-IP65	HEAVYCON ADVANCE IP65 protective cover B6, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet 3 mm


Diagrams/Drawings

Drilling plan/solder pad geometry



Panel cutout
 a = When self-tapping M4 Torx screws, diameter 3.6 mm are used, or when M4 screws with M4 thread or 4.5 mm diameter are used

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;