


HC-B 10-TMB-100/O1STM32G-STA

Order No.: 1604353

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604353>

HEAVYCON ADVANCE standard powder-coated sleeve housing
B10, with bayonet locking, height 100 mm, with 1xM32 thread, straight
cable outlet

Commercial data	
GTIN (EAN)	 4 017918 948030
sales group	D201
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 564 (PC-2011)

Product notes

WEEE/RoHS-compliant since:
01/31/2006

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data

General data

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	100 mm
Width	57 mm


Length	105 mm
Housing type	Sleeve housings
Locking type	Bayonet locking
No. of cable exits	1
Cable exit	Straight
Pg screw connection	None
Type of the screw connection	1x M32
Degree of protection	IP65/67
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel
Material grip body interlock	PA-GF
Length of the assembly cutout	65 mm
Width of the assembly cutout	35 mm

Accessories

Item	Designation	Description
Assembly		
1604641	HC-B-BF	Panel mounting flange for HEAVYCON ADVANCE TMB housing with bayonet locking
1604654	HC-B-BF-SET	Bayonet mounting-flange set, consisting of 2 mounting flanges with 4 self-tapping Torx head screws and 4 fan-type spacers
General		
1690943	HC-B 10-TMB-SD-IP65	HEAVYCON ADVANCE IP65 protective cover B10, with bayonet locking, with retaining cord, diameter of retaining cord eyelet 3 mm

Diagrams/Drawings

Dimensioned drawing



Panel cutout

²⁾ When self-tapping Torx screws are used
(Torx20, M4)

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;