

## Protective covers - HC-B 16-SD-FLU/FS-AL - 1644588

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective cover B16, for single locking latch, Protective cover material: Al, Seal: no, With lanyard, Diameter of retaining cord eyelet: 30 mm



### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 STK   |
| GTIN                                 | <br>4 017918 904906 |
| GTIN                                 | 4017918904906   |
| Weight per Piece (excluding packing) | 80.450 g  |
| Custom tariff number                 | 85389099  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|                                   |       |
|-----------------------------------|-------|
| Diameter of retaining cord eyelet | 30 mm |
|-----------------------------------|-------|

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Degree of protection            | IP65              |
| Ambient temperature (operation) | -40 °C ... 125 °C |

#### General

|              |   |
|--------------|---|
| Size         | B16   |
| Type         | For supporting base element with single locking latch |
| Material     | Aluminum, die-cast                                    |
| Seal present | no  |

## Protective covers - HC-B 16-SD-FLU/FS-AL - 1644588

### Technical data

#### General

|            |  |
|------------|--|
| Connection | The guide pins of the protective cover must be removed when using coding sockets, pins, and bolts. |
|------------|--|

### Approvals

#### Approvals

---

#### Approvals

#### EAC

---

#### Ex Approvals

---

### Approval details

|     |   |                     |
|-----|---|---------------------|
| EAC |  | 7500651.22.01.00246 |
|-----|---|---------------------|