

## Housing - HC-D 7-AML-24/GR/PA-A - 1647747


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel mounting base, with single locking latch, height 24 mm, with screw connection, PA reusable material, straight version, with metal strap



### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	250 STK
GTIN	 4 017918 942526
GTIN	4017918942526
Weight per Piece (excluding packing)	28.000 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	24 mm
Width	38 mm
Length	28 mm
Length of the assembly cutout	21 mm
Width of the assembly cutout	21 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP54
	IP65 (with sealing screw)
Ambient temperature (operation)	-40 °C ... 125 °C

# Housing - HC-D 7-AML-24/GR/PA-A - 1647747

## Technical data

### General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Panel mounting base, straight
Locking type	With single locking latch
Housing material	PA
Housing surface material	PA, light gray
Seal material	NBR
Material lock	Steel, galvanized

## Approvals

### Approvals

---

Approvals

EAC / GL

---

Ex Approvals

---

### Approval details

EAC		7500651.22.01.00246
-----	---	---------------------

GL		<a href="http://exchange.dnv.com/tari/">http://exchange.dnv.com/tari/</a>	6196614 HH
----	---	---	------------