


HC-B 10-KMQ-73/O1PG29

Order No.: 1678389

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1678389>

Coupling housing, with double locking latch, height 73 mm, without screw connection, 1x Pg29

Commercial data

GTIN (EAN)	 4 017918 151904
Note	Made-to-order
sales group	D002
Pack	7 pcs.
Customs tariff	85389099

Product notes

WEEE/RoHS-compliant since:
01/18/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	73 mm
Width	43 mm
Length	73 mm

Housing type	Coupling housings
Locking type	With double locking latch
Pg screw connection	None
Type of the screw connection	1x Pg29
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF

Certificates / Approvals




Certification

GOST

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;