

D-SUB sleeve housings - VS-09-T-20-1-S-S - 1655658

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

D-SUB sleeve housing, shell size 1, shielded, IP20 degree of protection



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 029544
Weight per Piece (excluding packing)	16.6 g
Custom tariff number	85389099
Country of origin	Hungary

Technical data

Mechanical characteristics

External cable diameter	4 mm ... 8.5 mm
Cable exit	straight
Color	Bare metallic
Mounting type	Screw locking

Ambient conditions

Ambient temperature (operation)	-20 °C ... 80 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Housing material	ABS
Housing surface material	Metal-plated

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

D-SUB sleeve housings - VS-09-T-20-1-S-S - 1655658

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 2.0	EC001133
ETIM 3.0	EC001133
ETIM 4.0	EC001133
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

D-SUB sleeve housings - VS-09-T-20-1-S-S - 1655658

Dimensional drawing

