

## D-SUB pressure nut - VS-PG11 (5-10) - 1688104

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB cap nut with line seal, for conductor diameter of 5 mm ... 10 mm, for sleeve housing VS-15-...



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	3.97 g
Custom tariff number	39269097
Country of origin	Germany

### Technical data

#### Mechanical characteristics

External cable diameter	5 mm ... 10 mm
Type of cable	Round cable
Color	gray

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	-20 °C ... 80 °C

#### Material data

Flammability rating according to UL 94	V0
Housing material	PA
Sealing material	Neoprene
Seal material	Neoprene

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## D-SUB pressure nut - VS-PG11 (5-10) - 1688104

### Classifications

#### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261203
eCl@ss 7.0	27440202
eCl@ss 8.0	27069215
eCl@ss 9.0	27144420

#### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000814

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

### Drawings

Dimensional  
drawing

D-  
SUB  
cap  
nut

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1688104](#)