



POS.	A <sup>-0.76</sup>	B1 <sup>-0.25</sup>	B2 <sup>+0.25</sup>	C	D <sup>-0.3</sup>	PART NO.
9	31.19	16.46	16.79	25.00 <sup>+0.12</sup> <sub>-0.13</sub>	6.12	163A50009X
15	39.52	24.79	25.12	33.30 <sup>+0.15</sup> <sub>-0.1</sub>	6.12	163A50019X
25	53.42	38.50	38.84	47.04 <sup>+0.13</sup>	5.99	163A50029X
37	69.70	54.96	55.30	63.50 <sup>+0.13</sup>	5.99	163A50039X

used for: D-SUB ADAPTER

**NOTES:**

1. METALSHELLS: STEEL; TIN PLATED
2. INSULATORS: PBTP GF UL 94 V-0
3. CONTACTS: COPPER ALLOY
4. PLATING: HARD GOLD OVER NICKEL
5. CONNECTOR IS PART MARKED: PART NO.: CONECC Y7/W7



tolerance		scale: 2:1 (5:1)	
dim. in mm		material: SEE NOTES	
2003	date	title: D-SUB ADAPTER	
drawn	28.02	9-37 pos.	
appd.	28.02.	[CAD/ 2000	
norm	DIN 41652	DIN-A	
6-old		3	
rev. description		date	
name		product no: SEE TABLE	
DO NOT ALTER CAD DRAWING BY HAND OWNERSHIP AND COPYRIGHT OF CONEC GMBH WRITTEN PERMISSION BE PASSED ON TO A THIRD PARTY WITHOUT REPRODUCED IN ANY WAY, AND MAY NOT THIS DRAWING MAY NOT BE COPIED OR			