




RF CONNECTOR LAUNCHERS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)
2052 3358 02
SM , SMA

1052643-1
TE Internal Number: 1052643-1

Always EU RoHS/ELV Compliant

RF Connector Type **SMA**

50 Ohm **Yes**

75 Ohm **No**

Applies To **Coaxial Cable**

Length **9.53 mm [.375 in]**

Product Drawings

OSM JACK 4 HOLE FLANGE ACCEPTS .036 DIA. PIN
PDF (TIFF AVAILABLE)
English

OSM JACK 4 HOLE FLANGE ACCEPTS .036 DIA. PIN
PDF (TIFF AVAILABLE)
English

CAD Files

3D PDF
PDF
3D

Customer View Model
2D_DXF.ZIP
English

Customer View Model
3D_IGS.ZIP
English

Customer View Model
3D_STP.ZIP
English

Catalog Pages/Data Sheets

SMA Connectors
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

RF Connector Type

SMA

Applies To

Coaxial Cable

Product Type

Launcher

Dielectric Material

TFE Fluorocarbon

Electrical Characteristics	50 Ohm	Yes
	75 Ohm	No
	Insulation Resistance (MΩ)	10000
Body Features	Body Plating Finish	Passivated
	Body Material	Stainless Steel
	Body Style	Straight
Contact Features	Center Contact Material	Beryllium Copper
	Pin Diameter Accepted	.91 mm [.036 in]
	Center Contact Plating Material	Gold
	Center Contact	With
	Captivated Contacts	With
	Captivation Method	Mechanical
Mechanical Attachment	Panel Mount Retention Type	Flanged
	Panel Attachment Style	Rear Mount
	Number of Panel Mounting Holes	4
Dimensions	Length	9.53 mm [.375 in]
Other	Comment	Field replaceable., Hermetic Terminals

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)