

Membrane Switch Printmount Short Stroke 18mm



Weblinks

[html-datasheet](#), [General Product Information](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [CAD-Drawings](#), [Product News](#), [Detailed request for product](#)

All Variants

Description	Order Number
MCS18	1241.1108

Availability for all products can be searched real-time:<http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>



DATA MCS 18 SWITCHES – MOMENTARY ACTION



BENEFITS

- Absolutely unique, extremely low design
- Almost flush with the front plate
- High-quality gold and silver contacts
- Excellent price/performance ratio
- Available with various colours and lettering
- Reliable tactile feedback
- Ideal switch for applications with 2 to 6 keypoints
- Suitable for highly versatile applications

	MCS 18 gold contacts	MCS 18 silver contacts
Electrical data		
Contact material	gold	silver
Switching voltage	min. 50 DC max. 24 DC	min. 5 V DC max. 48 DC
Switching current max.	80	125
Rated breaking capacity	0.36	0.72
Lifetime (at rated breaking capacity)	>10 ⁶	>10 ⁶
Initial contact resistance, new	< 50	< 50
Initial contact resistance, after lifetime	< 150	< 150
Insulation resistance	> 10 ⁸	> 10 ⁸
Contact bounce time	typ. 0.1	typ. 0.1
Mechanical data		
Actuating force	3 ± 1	3 ± 1
Contact travel	0.5 ± 0.1	0.5 ± 0.1
End stop strength	> 50	> 50
Lifetime	> 10 ⁶	> 10 ⁶
Other data		
Solderability	235 / 2	235 / 2
Soldering heat resistance	260 / 5	260 / 5
Ambient temperature	-25 – +60	-25 – +60
Storage temperature	-25 – +60	-25 – +60
Degree of protection	IP 65	IP 65
Materials		
Socket	Thermoplast PES	Thermoplast PES
Face foil	PETP	PETP
Bezel	Thermoplast PBTP	Thermoplast PBTP
Contact material gold / silver	CuZn 37, 3 µm Ni 2 µm Au	CuZn 37, 2.5 µm Ag

OVERVIEW MCS 18 SWITCHES—MOMENTARY ACTION



Specification for lettering, see page 29.	MCS 18	MCS 18	
---	--------	--------	--

FEATURES

Contact material	Ag	Au	
Degree of protection	IP 65	IP 65	

PART NUMBER *

square	1241.1108. x xxx	1241.1109. x xxx	xxx
round	1241.1110. x xxx	1241.1111. x xxx	xxx
Colour of bezel			
red	3	3	
grey	6	6	
black	7	7	
Colour of face foil without legend			
yellow	091	091	
red	093	093	
green	095	095	
grey	096	096	
black	097	097	
white	098	098	
Standard lettering			
Order index	see page 29	see page 29	

<p>Dimensions:</p>	<p>Drilling diagram:</p>	<p>Circuit diagram:</p>
--------------------	--------------------------	-------------------------

* X in the Part No. must be replaced by the desired version




LETTERING

Depending on the application and font, there are various lettering possibilities. The following standards can be used for key letterings:


ORDER INDEX LETTERING

A = 001	P = 016	4 = 031	↕ = 046	EIN = 061
B = 002	Q = 017	5 = 032	→ = 047	AUS = 062
C = 003	R = 018	6 = 033	← = 048	AUF = 063
D = 004	S = 019	7 = 034	↓ = 049	AB = 064
E = 005	T = 020	8 = 035	↑ = 050	ON = 065
F = 006	U = 021	9 = 036	% = 051	OFF = 066
G = 007	V = 022	+ = 037	√ = 052	UP = 067
H = 008	W = 023	- = 038	CTRL = 053	DOWN = 068
I = 009	X = 024	. = 039	RETURN = 054	HIGH = 069
J = 010	Y = 025	x = 040	SHIFT = 055	LOW = 070
K = 011	Z = 026	÷ = 041	LOCK = 056	ON/OFF = 071
L = 012	0 = 027	* = 042	STOP = 057	START = 072
M = 013	1 = 028	= = 043	ENTER = 058	
N = 014	2 = 029	# = 044	BACK = 059	
O = 015	3 = 030	↔ = 045	LINE = 060	



MCS 18, LETTER HEIGHTS AND FONTS

- Single characters, Univers 65
- Legends max. 6 characters in line, Univers 65
- Insert label and front foil anthracite, RAL 7016
- Characters and symbols light grey, RAL 7035



SSM 27, LETTER HEIGHTS AND FONTS

- Single characters, Univers 65
- Legends max. 6 characters in line, Akzident-Grotesk condensed bold type
- Front foil anthracite, RAL 7016
- Characters and symbols light grey, RAL 7035