



Mounting hole (inch)	0.3150"
Mounting hole (metric)	8mm
Indicator type	flashing
Mounting type	with bezel
Bezel type	recessed
Bezel material	metal
Bezel color	black chrome
Bezel size	M8
Protection	IP40
Lens type	round
Lens color	red diffused
Lens size	5mm
Connector Tpe	tab terminals 2.8x0.8mm
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	red
Dom wave length	625nm
Peak Wave Length (mA)	
Op. voltage (V)	24V DC
Forward volt max.	
Rectifier	-
AC current	-
DC current	38-56mA
Lum in min (mcd)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1905	Print date : 03/10/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19071353
Serial Number : 1905
LEDs Indicators

Lum in type (DC)	80mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	
ROHS Status	Yes

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1905	Print date : 03/10/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :