# 1825096-7 Product Details

# 1825096-7

TE Part Number: 1825096-7

Add to Part List

#### **Pushbutton Switches**

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### **Product Highlights:**

- Switch Mechanical
- Not Tactile
- · Single Pole Double Throw Configuration (Pole-Throw)
- Contact Rating = 0.4VA
- Operating Function = Momentary

View all Features | Find Similar Products

# <u>Availability</u>

Quick Links Check Pricing &

Live Product Chat

- Search for Tooling Product Feature
- Selector
- Contact Us About This Product

### **Documentation & Additional Information**

### Product Drawings:

PUSHBUTTON SWITCH, TPA SERIES (PDF, English)

# Catalog Pages/Data Sheets:

None Available

### **Product Specifications:**

None Available

### Application Specifications:

None Available

### Instruction Sheets:

None Available

# CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version A)
- 3D Model (IGES, Version A)
- 3D Model (STEP, Version A)

#### Additional Information:

• Product Line Information

#### Related Products:

Tooling

# List all Documents

# Product Features (Please use the Product Drawing for all design activity) Product Type Features:

- Product Type = Switch Mechanical
- Tactile = No
- Configuration (Pole-Throw) = Single Pole -Double Throw
- Mount Angle = Vertical
- Termination Type = Printed Circuit
- Actuator Style = Round

# **Electrical Characteristics:**

• Contact Rating = 0.4VA

# **Body Related Features:**

- Series = TPA
- Mount Style = Through-Hole
- Actuator Length (mm [in]) = 3.85 [0.152]
- Actuator Profile = Extended
- Actuator Color = Black
- Case Material = Polyester
- Actuator Material = Polyamide

# Contact Related Features:

• Contact Plating = Gold over Nickel

# **Housing Related Features:**

- Process Sealed = No
- Low Profile = No

### Configuration Related Features:

- Operating Function = Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Actuator Force (g [oz]) = 50.00 400.00 [1.770 14.120]
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

# Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

# Conditions for Usage:

Temperature Rating = High

# Packaging Related Features:

Packaging Method = Loose Piece

#### Other:

• Brand = Alcoswitch

# Provide Website Feedback | Need Help?