

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1706731200](#)  
**Status:** **Active**  
**Overview:** [EdgeLine® High Speed Connectors](#)  
**Description:** EdgeLine® Vertical Connector, 12.5 Gbps, 0.80mm Pitch, 1.57mm PCB Thickness, 1 Bay, 200 Circuits

**Documents:**

<a href="#">3D Model</a>	<a href="#">Application Specification AS-76693-101-001 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Packaging Specification PK-76693-900 (PDF)</a>
<a href="#">Product Specification PS-75594-999-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>
<a href="#">Application Specification AS-76693-100-001 (PDF)</a>	

**Agency Certification**

CSA	LR19980
UL	E29179

**General**

Product Family	Edge Card Connectors
Series	<a href="#">170673</a>
Application Tooling Part Link	62100-8500
Application Tooling Part Link	62201-8736
Circuit Size Range	65-200 Circuits
Component Type	Edgecard to PCB
Data Rate	12.5-20.0 Gbps
Edge Card Thickness	1.57mm
High Power Bay (30.0A or more)	No
Orientation	Vertical
Overview	<a href="#">EdgeLine® High Speed Connectors</a>
Product Name	EdgeLine®
Standard Based	General
UPC	884982404564

**Physical**

(p)ower-(s)ignal Configuration	200s - 0p
Circuits (Loaded)	200
Circuits (maximum)	200
Color - Resin	Black
Durability (mating cycles max)	200
Entry Angle	N/A
Flammability	94V-0
Keying to Mating Part	N/A
Material - Metal	Copper Alloy
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	10.025/g
PCB Locator	No
PCB Thickness - Recommended	2.79mm
Packaging Type	Tray
Pitch - Mating Interface	0.80mm
Pitch - Termination Interface	0.80mm
Plating min - Mating	0.762µm
Plating min - Termination	0.762µm
Polarized to Mating Part	Yes
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Through Hole - Compliant Pin



**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per  
-ED/01/2017 (12  
January 2017)

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

RoHS Phthalates

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[170673 Series](#)

**Electrical**

Current - Maximum per Contact 1.5A  
Voltage - Maximum 250V AC

**Solder Process Data**

Lead-free Process Capability N/A

**Material Info****Reference - Drawing Numbers**

Application Specification AS-76693-100-001, AS-76693-101-001  
Packaging Specification PK-76693-900  
Product Specification PS-75594-999-001  
Sales Drawing SD-170673-0001, SD-170673-1200  
Symbol/Footprint Data SYM-170673-1200

This document was generated on 02/17/2017

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**