



## Features:

- Tailored for emerging product designs
- Similar size to USB2.0 Micro-B
- Reversible plug orientation & cable direction
- Extended 5A current ranges plus USB Power delivery
- Designed to establish future USB performance needs
- High speed up to 10Gb/s

## Overview:

Amphenol's USB C type connectors, designed for emerging product designs are fully compliant to the newest C Type spec. The usability for these low profile connectors is enhanced by offering reversible plug and cable directions. The connectors also support scalable power charging by extending 5A current ranges plus USB power delivery.

## Applications:

### Smart Phones & Mobile Devices

- MP3 & music players
- Mobile phones
- Tablets, PCs, notebooks
- Portable charging bases
- Memory storage

### Automotive

- GPS systems/navigation
- Driver assistance systems
- Infotainment systems

### Consumer

- Copiers, printers, scanners
- Digital cameras, video cameras
- Digital & DVD media players
- LCD & TV panels
- Set top boxes

### Telecommunications

- Handsets
- ISDNs
- PBXs











To learn more about USB Type C connectors:

web: [amphenolcanada.com](http://amphenolcanada.com)

email: [sales@amphenolcanada.com](mailto:sales@amphenolcanada.com)

| Materials              |                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------|
| Contact                | Copper Alloy                                                                                          |
| Shell                  | Stainless Steel                                                                                       |
| Housing                | High Temperature Polymer UL94V-0, black                                                               |
| Plating                |                                                                                                       |
| Contacts               | Selective Plating in Contact Area;<br>Solder Tail Matter Tin Over Nickel; See drawing for More Detail |
| Shell                  | Nickel Plating                                                                                        |
| Coplanarity: 0.08 Max. |                                                                                                       |



Technical drawing of the Amphenol connector housing. The drawing shows a top view of the housing with dimensions: 9.20 (width), 10.50 (height), and 9.18 (width of the central section). The Amphenol logo is visible on the central section.

