




WIRE-TO-BOARD CONNECTOR CONTACTS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

SHORT POINT RECP CONT LP

AMPMODU | AMPMODU IV/V

104479-6

TE Internal Number: 104479-6

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Contact Type **Socket**

Wire/Cable Size (AWG) **24 – 20**

Wire/Cable Size (mm²) **.2 – .6**

Contact Mating Area Plating Material **Gold**

Contact Current Rating (A) **3**

Product Drawings

[CONTACT, CRIMP SNAP-IN AMPMODU SHORT POINT, 20-24 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Product Specifications

Product Specification

[Connector, Short Point Receptacle Contact](#)

PDF
English

Application Specification

[AMPMODU Short Point Contacts And Housings](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Wire/Cable Type

Discrete Wire

Product Type

Contact

Applied Pressure

Standard

With Insulation Support **Yes**

Applies To **Wire/Cable**

Electrical Characteristics	Termination Resistance	12 mΩ
	Operating Voltage (VAC)	300
	Dielectric Withstanding Voltage (V)	750
	Insulation Resistance (MΩ)	5000

Contact Features	Contact Type	Socket
	Contact Mating Area Plating Material	Gold
	Contact Current Rating (A)	3
	Contact Style	Crimp Snap-In
	Contact Mating Area Plating Thickness (μin)	15
	Contact Base Material	Copper Alloy C7025
	Contact Transmits (Typical)	Signal (Data)/Power

Termination Features	Termination Method to Wire/Cable	Crimp
	Crimp Area Plating Thickness (μin)	50
	Crimp Area Plating Material	Tin-Lead over Nickel

Dimensions	Wire/Cable Size (AWG)	24 – 20
	Wire/Cable Size (mm ²)	.2 – .6
	Insulation Diameter	.64 – 1.52 mm [.025 – .06 in]

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
------------------	----------------------------------	------------------

Industry Standards	Approved Standards	CSA LR7189, UL E28476
--------------------	--------------------	------------------------------

Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	500

Product Compliance [Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD CONNECTOR HOUSINGS

WIRE-TO-BOARD CONNECTOR HOUSINGS


POWER CONTACTS

WIRE-TO-BOARD CONNECTOR HOUSINGS

HOUSINGS



06 MTE RCPT HSG SR
LATCH .100
104257-5

 Save to List

 Find Similar Products

HOUSINGS

20 SHORT PT RCPT HSG
DR .100CL
104482-9

 Save to List

 Find Similar Products

PIN CONT 20-24 TIN PLATE
L/P
1-794612-0

 Save to List

 Find Similar Products

HOUSINGS



12 AMPMODU MT ASSY
DR.100CL SN
5-102448-4

 Save to List

 Find Similar Products

