

## PCB D-SUB CONNECTORS

У 🖬 f v



✓ Active



TE CONNECTIVITY (TE) 09 PLUG SP/FMS SCRLK AMPLIMITE | FSM , SP

**1-5747871-3** TE Internal Number: 1-5747871-3

Always EU RoHS/ELV Compliant

Connector Style **Plug** Centerline (in) **.108** Number of Positions **9** 

Number of Rows **2** 

Shell Size 1

Product Drawings	PLUG ASSEMBLY, SIZE 1, 9 POS, VERTICAL, FRONT SHELL, AMPLIMITE HDP PDF English		
CAD Files	Customer View Model 2D_DXF.ZIP English		
	Customer View Model		
	3D_IGS.ZIP <b>English</b>		
	Customer View Model		
	3D_STP.ZIP English		
	3D PDF		
	PDF English		
Catalog Pages/Data Sheets	AMPLIMITE Subminiature D Connectors - Straight Posted Connectors PDF English		
Product Specifications			
Product Specification	AMPLIMITE HD-20 PCB Mounted Connector		
Application Specification	<b>English</b> AMPLIMITE HD-20 Straight Solder Contact Tine, Front Metal Shell, PC Board And Panel Mount Connectors PDF		
Qualification Test Report English   Qualification Test Report Connector, AMPLIMITE HD-20, Printed Circuit Board Mounted   PDF English   English English			

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Plug
	Shell Size	1
	Profile	Standard
	PCB Mounting Orientation	Vertical
	Grounding Straps	Without
	Shell Type	Front Metal Shell
	Grounding Indents	With
	Applies To	Printed Circuit Board
	Sealed	No
	Grounded	Yes
	Product Type	Connector
Configuration Features	Number of Positions	9
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	Νο
	Female Screwlock Material	Zinc
	Color Code	None
	Shell Plating Material	Tin
	Shell Material	Steel
	Post Size	.66 mm [ .026 in ]
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Brass
	Contact Mating Area Plating Material	Gold Flash
Termination Features	Termination Post Length	3.18 mm [ .125 in ]
	Grounding Clips	Without
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Mounting Holes
	Mating Connector Lock	With
	Mating Connector Lock Type	Female Screwlocks, Fixed

	Panel Mount Retention Mounting Hole Diameter	Without 3.05 mm [ .12 in ]
Housing Features	Centerline (in) Housing Color Housing Material	.108 Black Thermoplastic
Dimensions	PCB Thickness (Recommended)	1.57 – 2.36 mm [ .062 – .093 in ]
Industry Standards	UL Flammability Rating Approved Standards	UL 94V-0 UL E28476
Packaging Features	Packaging Method Packaging Quantity	Tube 17
Other	Comment	Plugs are preloaded with size 20 DF posted pin contacts
Product Compliance	Statement of Compliance PDF	

VIEW ALL PRODUCT COMPLIANCE

# CUSTOMERS ALSO BOUGHT

PCB D-SUB CONNECTORS	FUSION TAPE	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	RECTANGULAR POWER CONNECTORS
	A		
15 RCPT SP/FMS SCRLK 1-5747299-6	FUSION TAPE, 1" X .020" X 10FT 605262-1	08 MODII HDR SRST SHRD .100CL 103414-6	09P UMNL HDR ASSY PC NATL LF 350586-4
<ul><li>Save to List</li><li>Find Similar Products</li></ul>	Save to List	<ul><li>Save to List</li><li>Find Similar Products</li></ul>	<ul><li>Save to List</li><li>Find Similar Products</li></ul>

Products - 5 Results		View All	Compare 0/10 🛭 🗲		
	Relation Type	•			

#### RELATIONSHIP **Mating Products** Used to identify Mating Parts

See All Mating Products

See All Mating Products

See All Mating Products



#### RELATIONSHIP **Mating Products** Used to identify Mating Parts



PRODUCT - MATING PRODUCTS

Connectors - Solder D-Sub Connectors AMPLIMITE I Solder Cup Connectors LF RECEPT KIT, SIZE 1, 7.2MM - 1571654-4 TE INTERNAL NUMBER: 1571654-4

✓ Active



Always EU RoHS/ELV Compliant

Connector Style **Receptacle** Number of Positions **9** Contact Size **20** Shell Size **1** Enclosure **With** 

### RELATIONSHIP Mating Products Used to identify Mating Parts



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE I HDE (IDC) Insulation 09 HDE MS RCPT, 22-26, LEAD FREE - 1-745491-8 TE INTERNAL NUMBER: 1-745491-8

✓ Active

#### Always EU RoHS/ELV Compliant

Connector Style **Receptacle** Number of Positions **9** Number of Rows **2** Preloaded **Yes** Contact Size **20**