



## STANDARD RECTANGULAR CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
Japanese

↓ **3D PDF**

TE CONNECTIVITY (TE)

### DYNAMIC DBL ROW HDR ASSY 12P V

Dynamic Series | Dynamic 3000 Series

178326-2

TE Internal Number: 178326-2

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Polarization**

Mating Retention **With**

Mating Retention Type **Latch**

#### Product Drawings

[12 POS DOUBLE ROW VERTICAL HDR ASS'Y FOR DYNAMIC D-3100](#)

PDF (**TIFF AVAILABLE**)

Japanese

[12 POS DOUBLE ROW VERTICAL HDR ASS'Y FOR DYNAMIC D-3100](#)

PDF (**TIFF AVAILABLE**)

Japanese

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP

English

[Customer View Model](#)

3D\_IGS.ZIP

English

[Customer View Model](#)

3D\_STP.ZIP

English

[3D PDF](#)

PDF

English

#### Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors](#)

PDF

English

[1-1773732-4\\_DYNAMIC\\_SERIES\\_CATALOG\\_ENGLISH](#)

PDF

English

#### Product Specifications

##### Product Specification

[Dynamic Connector D-3000 Series](#)

TIF

Japanese

[Dynamic Connector D-3000 Series](#)

PDF

Japanese

##### Qualification Test Report

[DYNAMIC D-3000 SERIES CONNECTOR](#)

PDF

Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	<b>Connector</b>
	PCB Mounting Orientation	<b>Vertical</b>
	Sealed	<b>No</b>
	Connector System	<b>Wire-to-Board</b>
	Shielded	<b>No</b>
	Insertion Force	<b>Standard</b>
	Row-to-Row Spacing	<b>5.08 mm [ .2 in ]</b>
	Connector Style	<b>Plug</b>
	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	Strain Relief	<b>Without</b>
	Series Number	<b>3000</b>
	Shrouded	<b>Yes</b>
	Connector Type	<b>Header</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features	Number of Positions	<b>12</b>
	Number of Rows	<b>2</b>
	Preloaded	<b>Yes</b>
	Selectively Loaded	<b>No</b>

---

Electrical Characteristics	Operating Voltage	<b>250 VAC [ 250 VDC ]</b>
	UL Voltage Rating	<b>250 VAC [ 250 VDC ]</b>

---

Body Features	Header Type	<b>Shrouded</b>
	Sealable	<b>No</b>

---

Contact Features	Contact Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>15</b>
	Tail Plating Thickness	<b>2 <math>\mu</math>m [ 78.74 <math>\mu</math>in ]</b>
	Multiple Contact Types	<b>Without</b>
	Contact Style	<b>Straight</b>
	Contact Type	<b>Tab</b>
	Tail Plating Material	<b>Tin</b>

	Termination Method to PC Board	<b>Through Hole - Solder</b>
Mechanical Attachment	Mating Alignment	<b>With</b>
	Mating Alignment Type	<b>Polarization</b>
	Mating Retention	<b>With</b>
	Mating Retention Type	<b>Latch</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Retention Leg</b>
	Contact Retention	<b>Without</b>
	PCB Mount Alignment	<b>Without</b>
Housing Features	Centerline	<b>3.81 mm [ .149 in ]</b>
	Housing Material	<b>Polyester GF</b>
	Housing Color	<b>Black</b>
Dimensions	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Tail Length	<b>3.8 mm [ .149 in ]</b>
	Height	<b>21.6 mm [ .85 in ]</b>
	Width	<b>14.43 mm [ .568 in ]</b>
	Length	<b>33.05 mm [ 1.3 in ]</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
Operation/Application	For Use With	<b>Receptacle Housing</b>
	Assembly Integration Feature	<b>Without</b>
	Halogen Free	<b>Yes</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	CSA File Number	<b>LR7189</b>
	VDE Tested	<b>No</b>
	CSA Rating	<b>Certified</b>

UL Rating	<b>Recognized</b>
Agency/Standard	<b>CSA, UL</b>
UL File Number	<b>E28476</b>





Packaging Features	Packaging Quantity	<b>15</b>
	Packaging Method	<b>Tube, Tube/Box</b>

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

<p><b>STANDARD RECTANGULAR CONNECTORS</b></p>  <p><b>DYNAMIC D-3 HDR ASSY V 20P</b> 178328-2</p> <p><a href="#">Save to List</a></p> <p><a href="#">Find Similar Products</a></p>	<p><b>RECTANGULAR CONNECTOR HARDWARE</b></p>  <p><b>DYNAMIC PUSH RIVET 900128-1</b></p> <p><a href="#">Save to List</a></p> <p><a href="#">Find Similar Products</a></p>	<p><b>STANDARD RECTANGULAR CONNECTORS</b></p>  <p><b>DYNAMIC 3100 HDR V 10P ASSY Y</b> 2-178318-2</p> <p><a href="#">Save to List</a></p> <p><a href="#">Find Similar Products</a></p>	<p><b>STANDARD RECTANGULAR CONNECTORS</b></p>  <p><b>10-P POST HDR D-3100D VERT .38</b> 178325-2</p> <p><a href="#">Save to List</a></p> <p><a href="#">Find Similar Products</a></p>
--	---	---	--