



CONNECTORS

POWER CONTACTS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

III+ SKT, 18-14, 30AU/FL, LP

AMP | Type III+ - Enhanced High Current

1-66601-0

TE Internal Number: 1-66601-0

Always EU RoHS/ELV Compliant

Product Type **Contact**

Wire/Cable Size (AWG) **18 - 14**

Wire/Cable Size (mm²) **.8 - 2**

Circuit Application **Signal**

Contact Type **Socket**



Product Drawings

SOCKET ASSEMBLY, LOOSE PIECE, TYPE III+

PDF
English

CAD Files

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Catalog Pages/Data Sheets

Signal Contacts

PDF
English

AMP Circular Connectors For Commercial Signal & Power Applications

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Contact
Contact Features	Contact Type	Socket
	Contact Base Material	Copper Alloy
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	30
	Contact Termination Area Plating Material	Gold Flash
	Contact Size	16
Termination Features	Wire/Cable Size (AWG)	18 – 14
	Wire/Cable Size (mm²)	.8 – 2
	Termination Type	Crimp
Dimensions	Accepts Wire Insulation Diameter Range	2.79 – 3.81 mm [.11 – .15 in]
Operation/Application	Circuit Application	Signal
Packaging Features	Packaging Method	Carton, Loose Piece
	Packaging Quantity	1000
Other	Comment	Contacts can only be used in Metrimate, Series 1 (Arr. 23-24), Series 4 (Arr. 23-13M, 23-16M, 23-22M), and VDE connectors.
	For Use With	CPC Connectors, VDE Connectors
	Wire/Cable Type	Discrete Wire
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	



