

REV. 0


DCO 141053

COIL: @ 25°C
 RESISTANCE 200 OHMS ± 10%
 NOMINAL VOLTAGE 6.0 VDC
 MUST OPERATE 3.4 VDC
 MUST RELEASE 2.0 VDC MAX, 0.28 VDC MIN.

ENVIRONMENT:
 VIBRATION 10 CPS TO 3000 CPS @ 30 g's
 SHOCK 75 g's 6 MS. DURATION
 TEMPERATURE -65 °C TO +125 °C

NOTES: OPERATE TIME 4.0 MS MAX
RELEASE TIME 7.5 MS MAX
CONTACT STABILIZATION 2.5 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1 AMP
28 VDC RESISTIVE 100,000 OPERATIONS MIN

DR. B.D. 5/10/99 *CK. FERR* 5/10/99

COMMUNICATIONS - INSTRUMENTS, INC.

CUST. QPL
 CUST. NO. M39016/42-034P

TYPE JMGSD RELAY

JMGSCD-6P

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGSCD-6P](#)