



CONNECTORS

## STANDARD RECTANGULAR CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### DYNAMIC 3100 HDR H 3P ASSY

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-178293-2

TE Internal Number: 1-178293-2

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Keyed**

Mating Retention **With**

Mating Retention Type **Latch**



#### Product Drawings

[3 POS SINGLE ROW HORIZONTAL HDR ASS'Y FOR DYNAMIC 3100](#)

PDF (**TIFF AVAILABLE**)

English

[3 POS SINGLE ROW HORIZONTAL HDR ASS'Y FOR DYNAMIC 3100](#)

PDF (**TIFF AVAILABLE**)

English

#### CAD Files

[3D PDF](#)

PDF  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors](#)

PDF  
English

---

## Product Specifications

Product Specification	<a href="#">Dynamic Connector D-3000 Series</a> TIF Japanese
Qualification Test Report	<a href="#">Dynamic Connector D-3000 Series</a> PDF Japanese <b>DYNAMIC D-3000 SERIES CONNECTOR</b> PDF Japanese

---

## Product Environmental Compliance

TE Material Declaration	<a href="#">MD_1-178293-2_08032012940</a> PDF English
-------------------------	---

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	Connector
	PCB Mounting Orientation	<b>Right Angle</b>
	Sealed	<b>No</b>
	Connector System	<b>Wire-to-Board</b>
	Shielded	<b>No</b>
	Insertion Force	<b>Standard</b>
	Connector Style	<b>Plug</b>
	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	Strain Relief	<b>Without</b>
	Series Number	<b>3000</b>
	Shrouded	<b>Yes</b>
	Connector Type	<b>Header</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features		
	Number of Positions	<b>3</b>
	Number of Rows	<b>1</b>
	Preloaded	<b>Yes</b>
	Keying	<b>X</b>
	Selectively Loaded	<b>No</b>

---

Electrical Characteristics	Operating Voltage	<b>250 VAC [ 250 VDC ]</b>
----------------------------	-------------------	----------------------------

Body Features	Header Type	<b>Shrouded</b>
	Sealable	<b>No</b>
Contact Features	Contact Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>12</b>
	Tail Plating Thickness	<b>2 <math>\mu</math>m [ 78.74 <math>\mu</math>in ]</b>
	Multiple Contact Types	<b>Without</b>
	Contact Style	<b>Right Angle</b>
	Contact Type	<b>Tab</b>
	Tail Plating Material	<b>Tin</b>
	Contact Transmits (Typical)	<b>Power, Signal (Data)</b>
	Shunts/Shorting Bars	<b>Without</b>
	Contact Layout	<b>Inline</b>
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
Mechanical Attachment	Mating Alignment	<b>With</b>
	Mating Alignment Type	<b>Keyed</b>
	Mating Retention	<b>With</b>
	Mating Retention Type	<b>Latch</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Retention Leg</b>
	Contact Retention	<b>Without</b>
	PCB Mount Alignment	<b>Without</b>
Housing Features	Lock Type	<b>Latch</b>
	Centerline	<b>3.81 mm [ .149 in ]</b>
	Housing Material	<b>Polyester GF</b>
Dimensions	Housing Color	<b>Black</b>
	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Tail Length	<b>3.8 mm [ .149 in ]</b>
	Height	<b>9.35 mm [ .368 in ]</b>
	Width	<b>22.1 mm [ .87 in ]</b>
	Length	<b>21.62 mm [ .851 in ]</b>

Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
------------------	-----------------------------	--------------------------------------

---

Operation/Application	For Use With	<b>Receptacle Housing</b>
	Assembly Integration Feature	<b>Without</b>
	Halogen Free	<b>Yes</b>

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	CSA File Number	<b>LR7189</b>
	CSA Rating	<b>Certified</b>
	UL Rating	<b>Recognized</b>
	Agency/Standard	<b>CSA, UL</b>
	UL File Number	<b>E28476</b>

---

Packaging Features	Packaging Quantity	<b>23</b>
	Packaging Method	<b>Tube, Tube/Box</b>

---

Product Compliance	<a href="#">Statement of Compliance</a> PDF
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>

