


**Product Details for 1 -1337541 -0**



**1 -1337541 -0**

[Active](#)

**BNC RF Connectors**

[RoHS Compliant \(Statement of Compliance\)](#)

**Product Highlights:**

- ? Connector
- ? Connector Type = ZDC/BNC
- ? Jack Receptacle
- ? Terminate To Printed Circuit Board
- ? Not Stacked

[View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [BNC STRAIGHT INSULATED PCB SOCKET 50 OHM WHITE](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? None Available

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? None Available

**CAD Files:**

- ? None Available

[List all Documents](#)

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

**Product Features**

(Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? [Product Type](#) = Connector
- ? Connector Type = ZDC/BNC
- ? Gender = Jack Receptacle
- ? [Stacked](#) = No
- ? [Number of Ports](#) = 1
- ? [Body Style](#) = Straight
- ? [PCB Mount Angle](#) = Vertical
- ? [Grade](#) = Commercial
- ? [PCB Height \(mm \[in\]\)](#) = 34.90 [1.374]
- ? [PCB Retention Feature](#) = With
- ? PCB Retention Method Feature = Solder Pin
- ? Mounting Post Style = Straight
- ? Mounting Post Length (mm [in]) = 4.30 [0.169]
- ? [Body Material](#) = Zinc
- ? [Body Insulation](#) = With
- ? [Sealed](#) = No
- ? [Isolated](#) = No
- ? [Dielectric Material](#) = Polyethylene
- ? [Color](#) = White
- ? Panel Thickness (mm [in]) = 1.50 - 5.50 [0.059 - 0.217]
- ? PCB Thickness (mm [in]) = 3.20 [0.126]

**Mechanical Attachment:**

- ? Surface Mountable = No
- ? [Panel Attachment](#) = With
- ? [Panel Attachment Method](#) = Bulkhead, Hex Nut
- ? Panel Attachment Style = Rear Mount
- ? Panel Cutout = 12.0mm x 12.9mm D -Shape
- ? Flange and Thread Material = PBT Polyester
- ? Flange and Thread Material Color = White

**Electrical Characteristics:**

- ? [Connector Impedance \(?\)](#) = 50

**Body Related Features:**

- ? [Hardware Included](#) = No
- ? [Body Plating](#) = Nickel
- ? [Polarized](#) = No
- ? PCB Tail Length (mm [in]) = 5.80 [0.228]

**Contact Related Features:**

- ? [Center Contact Material](#) = Brass
- ? [Center Contact Plating](#) = Gold

**Housing Related Features:**

- ? Housing Material = PBT Polyester

**Industry Standards:**

- ? Government/Industry Qualification = No
- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

**Conditions for Usage:**

- ? [Terminate To](#) = Printed Circuit Board
- ? Operating Temperature (Max.) (°C) = 85

**Packaging Related Features:**

- ? Packaging Method = Individual

**Other:**

- ? Brand = Greenpar