

Base strip - IPCV 5/ 4-G-7,62 - 1708844

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 41 A, Rated voltage (III/2): 630 V, Number of positions: 4, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Mounting: Soldering


The figure shows a 5-pos. version of the product

Why buy this product

- ✓ Asymmetrical arrangement of solder pins to prevent mismatching
- ✓ Inverted vertical IPC 5 headers for implementing a touch-proof PCB output or a PCB/PCB connection (in combination with PC 5 base strips)
- ✓ Maximum contact reliability due to integrated double steel spring



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| GTIN |  4 046356 089784 |
| Weight per Piece (excluding packing) | 10.89 g |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|----------------|----------|
| Length | 12.8 mm |
| Pitch | 7.62 mm |
| Dimension a | 22.86 mm |
| Pin dimensions | 1,2x0,8 |
| Pin spacing | 7.62 mm |
| Hole diameter | 1.3 mm |

General

| | |
|-----------------------------|--------------|
| Range of articles | IPCV 5/...-G |
| Insulating material group | I |
| Rated surge voltage (III/3) | 6 kV |

Base strip - IPCV 5/ 4-G-7,62 - 1708844

Technical data

General

| | |
|---|--------|
| Rated surge voltage (III/2) | 6 kV |
| Rated surge voltage (II/2) | 6 kV |
| Rated voltage (III/3) | 630 V |
| Rated voltage (III/2) | 630 V |
| Rated voltage (II/2) | 1000 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 41 A |
| Maximum load current | 41 A |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Color | green |
| Number of positions | 4 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals

Approvals

Base strip - IPCV 5/ 4-G-7,62 - 1708844

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized

| | | B | C | D |
|--------------------------------|-------|-------|-------|---|
| Nominal current I _N | 41 A | 41 A | 5 A | |
| Nominal voltage U _N | 300 V | 300 V | 600 V | |

cUL Recognized


| | | B | C | D |
|--------------------------------|-------|-------|-------|---|
| Nominal current I _N | 41 A | 41 A | 5 A | |
| Nominal voltage U _N | 300 V | 300 V | 600 V | |

EAC

cULus Recognized

Drawings

Drilling diagram



Dimensioned drawing

